

LED lighting kit made up of stabilized power PSU, n.2 magnetic LED and fastening clip.



cod. LED: M021020J     **IP40**

cod. PSU: A5LED5W    **IP40 dimmable**

cod. PSU: A8LED5W    **IP40**

K5LED1W: M021020J + A5LED5W (dimmable)

K10LED1W: M021020J + A8LED5W

ELECTRICAL FEATURES

Voltage	7,6 Vdc
Current	250~350 mA dc
Power	2x1W
IEC class	II

MECHANICAL AND OPTICAL FEATURES

LED type	Cree XR-E
N. LED	2
LED lifetime	50000 h
Brightness	Narrow beam - Max 25Lumen
Light colour	5000 °K
Spotlight LED	25x25x14mm
Fastening	Magnetic
Switch	Embodied in PSU
Degree of protection	IP40
Colour	Black

PSU FEATURES

Code	Vin	Vout	Iout	W	Size
A5LED5W dimmable	230 Vac	7,6 Vdc	350mA	3 W	90x55x50mm
A8LED5W	230 Vac	7,6 Vdc	260mA	5 W	90x55x50mm

ORDER CODES

M021020J	spotlight LED
A5LED5W	PSU dimmable for M021020J (K5)
A8LED5W	PSU for M021020J (K10)

Flow light from working surface

H 220mm

∅ (mm)	lux
150	560 lux
200	250 lux
240	180 lux

H 500mm

∅ (mm)	lux
245	260 lux
350	170 lux
450	140 lux