# **MYROS**






Extra-slim recessed luminaire for industrial machines tools. Provides precise and comfortable light to the work area.

- Extra-slim housing made of aluminum alloy
- Extra clear tempered front glass with internal PMMA diffuser
- High grade of protection IP67 with M12 connector
- Protection from reverse polarity
- Operating temperature from -20°C to + 45°C
- LED lifespan > 60,000 h (L 70)
- Light color 5,000 K CRI 80
- 24 Vdc power supply via M12

### **DIMENSIONS**



#### **MECHANICAL FEATURES** Model MY0121S01 Casing Material Anodized extruded aluminum Surface Treatment Standard: 10 microns of natural aluminum solution oxidation Front Glass Extra clear tempered 0.16 in (4 mm) thick glass Weight (excluding ~2.20 lb accessories) 0.95 kg **Protection Index** IP67 Impact Resistance IK06 -4°F (-20°C) to +113°F (+ 45°C) **Operating Temperature** Installation Screws

0

ELECTRICAL FEATURES		
Model	MY0121S01	
Power Input	10,5 W	
Power Supply	22 ÷ 26 Vdc	
Current	0,46 A	
Device Power Protection	Protection against reverse polarity	
Electrical Connection	M12-A 4P M connector	
Insulation Class	Class III (SELV)	


CONNECTION* with M12-4P Male A Codi	ng		
Male	Female	Pin	Connection
		1	+24 Vdc
2 - 1	1-50-2	2	Not Connected
3	4-0-3	3	0 Vdc
V-		4	Not Connected


OPTICAL FEATU	RES						
Model	N° and Type of LEDs	LED Lifespan	Light Color	CRI	Light Beam Angle	Luminous Flux	Efficiency
MY0121S01	30 Mid Power LED	60 000 h L70 **	5000 K	80	Diffuse 120°	~ 900 lm	~ 86 lm/W

<sup>\*\*</sup> Flow beam reduced by less than 30% after 60,000 hours

## **PHOTOMETRIC DIAGRAMS**

120° Flow beam MY0121S01





Distance graphic: 1m

## PLUG OPTION M12 Cable Connector

Product pictures Description Code product



M12 4P (F) COD.A with cable L.16ft (5m)

M12AFC5UL

ORDER CODES	
Model	Description
MY0121S01	MYROS, 226mm, 120°, 13W, 24Vdc, M12-A Male, Silver
M12AFC5UL	PRE-ASSEMBLED M12 4Pin. FEMALE. A Coding. CABLE 5mt. UL