



Compact lighting apparatus made up of aluminum illuminator covered by anti-heat ABS case, 3 power LED sources with 8°-25°-40° lens, head swivel, aluminum base with fastening holes, unipolar switch positioned back on the head lamp. External LED driver. Power supply 230V 50/60Hz. Current 350mA.



Application: particularly suitable for the lightning of drilling machines and lathes.

ELECTRICAL FEATURES

Voltage	12 Vdc
Current	350mA dc
Power	3 W
IEC class	II
Cable lenght	1,5 m

MECHANICAL AND OPTICAL FEATURES

LED type	Cree XR-E
N. LED	3
LED lifetime	50 000 h
Brightness	Narrow beam (8°-25°-40° lens)
Light colour	5300 K
Spotlight	Ø70x80mm
Base	60x60xH36mm
Fastening	4 screws
Switch	Unipolar on-off on the spot
Degree of protection	IP30
Colour	Black

LED DRIVER FEATURES

Cod.	Vin	Vout	In dc	P	Size
A13350TC	230Vac	12Vdc	350mA	4W	60x35x21mm
separated from lamp					

ORDER CODES

Cod.	Voltage	Lamp colour	Lens
LBC1050.08	12Vdc	Black	8°
LBC1050.25	12Vdc	Black	25°
LBC1050.40	12Vdc	Black	40°



Flow light from working surface (40° lens)

H 220mm

Current	350mA
Ø (mm)	lux
60	10800
120	3400
180	1000

H 500mm

Current	350mA
Ø (mm)	lux
105	2280
240	1180
380	430



Dimensions

A -	80mm
B -	Ø70mm
C -	60mm
D -	60mm
E -	36mm
F -	220mm