

series TKPL 230V

LED lamp for quality control



C.C.E.A. s.r.l
Via Plave, 2
36077 Altavilla Vicentina (VI) - Italy
Tel. ++39 0444 572083
Fax. ++39 0444 572337
E-mail: ccea@ccealights.com
www.ccealights.com



Also available with panel M12 4P (M) connector.
To be ordered separately.

LED lamp for quality control.


Solid anodized aluminum structure with conical de-glaring prism in PMMA.

High efficiency white homogeneous light 5000K.

New LED Technology with smart electronics.

Power supply 230VDC. Built-in AC/DC converter.

Two versions lenght available.



High efficiency, smooth de-glaring with opal appearance are the key features of this product.



Built-in Converter AC/DC
230/24Vdc 60W 2,5A.

cod. TKPL5.50

cod. TKPL8.50

Electrical features

Power supply

210-230V 50/60Hz
(built-in converter 230-24V)

Watt

34 W

Current

1,5 A

LED Driver

built-in on the PCB LED

IEC class

I

210-230V 50/60Hz

(built-in converter 230-24V)

55 W

2,4 A

built-in on the PCB LED

I

Optical features

LED type

SEOUL 5630

LED-Nr.

n.5 PCB with 18 LED (90 led tot.)

LED lifetime

50 000h.

Lumen LED

3500 lm

Light color

5000 K

Chromatic rendering index CRI

75

SEOUL 5630

n.8 PCB with 18 LED (144 led tot.)

50 000h.

5600 lm

5000 K

75

Mechanical features

Structure

Anodized aluminium

Covering

Conical de-glaring prism PMMA 3mm

Degree of protection

IP67

Color

Aluminum


Anodized aluminium

Conical de-glaring prism PMMA 3mm

IP67

Aluminum

DIMENSIONS (all values in mm)



FASTENING



art. TK-FX02

Side plates of stainless steel fastening

	A	B	C
TKPL5.50	65	840	46
TKPL8.50	65	1200	46