

UniOP eTOP32B

The eTOP32B is a cost-effective HMI device with touchscreen interface and 9.6" monochrome LCD display. The VGA resolution makes it the ideal choice for HMI applications demanding a large display on a limited budget.



- 9.6" monochrome display
- 8 grey levels
- VGA (640x480 pixel) resolution
- Resistive touchscreen
- Connection to industrial bus systems and Ethernet (requires optional plug-in modules)
- 32 MB internal user memory

Highlights

The eTOP HMI panels are part of the UniOP family of touchscreen products. All of the eTOP products support the rich common functionalities of the UniOP operator panels:

- Powerful and intuitive programming with the UniOP Designer 6 software
- Support of more than 130 communication drivers for industrial devices
- Optional modules for fieldbus systems (Profibus DP, CANopen, DeviceNet, Interbus) and Ethernet. Ethernet modules allow connection to field devices as well as programming the HMI from Designer.
- Dual-driver communication capability
- Vector graphic capabilities including the support of multiple layers and object transparency.
- Display dynamic data in numerical, text, bargraph and graphic image formats
- Data acquisition and trend presentation. Trend data can be transferred to a host computer using the Ethernet connection.
- Analog gauge objects
- Recipe data storage. Recipe data can be transferred to a host computer using the Ethernet connection.
- Multilanguage applications. The number of runtime languages is limited only by the available memory. All text information in

the application can be exported in Unicode format for easier translation.

- Powerful macro editor to configure touchscreen operation
- Alarms and historical alarm list. Alarm and event information can be printed or transferred to a host computer using the Ethernet connection.
- Eight level password protection.
- Report printing to serial printer. Reports are freely configurable using Designer.
- Ethernet-based UniNet network to share data between UniOP HMIs and to serve data using UniNet OPC Server.

AUDIN - 8, avenue de la malle - 51370 Saint Brice Courcelles

Tel : 03.26.04.20.21 - Fax : 03.26.04.28.20 - Web : <http://www.audin.fr> - Email : info@audin.fr

tn217-0.doc - 8.04.2005

UniOP eTOP32B

Technical Data

Display			
Type	Monochrome LCD, 8 grey levels	Recipe memory	32 KB
Resolution	VGA, 640x480 pixel	UniNet network	Client/Server
Active display area	196x147 mm (9.6" diagonal)	Alarms	1024
Colors	-	Event list	1024
Backlight	CCFL	Password	Yes
Brightness	100 cd/m ² typ.	Hardware RTC	Yes, battery backed
Dimming	Yes	Screen saver	Yes
Memory		Buzzer	Yes, audible feedback for touch screen
User memory	32 MB internal Flash	Battery	3 V 270 mA Lithium, non rechargeable, user replaceable, model CR2430. Replace with same component or equivalent compatible with the operating temperature of the product.
User memory expansion	Optional removable 32 MB SSFDC memory card		
Front panel			
Touch screen	Analog resistive		
Function keys	1		
System keys	-		
User LED's	1		
System LED's	4		
Interfaces			
PC/Printer port	Yes		
PLC port	RS-232, RS-485, RS-422, 20 mA Current Loop		
Aux port (fieldbus and Ethernet)	Yes, with optional modules		
DX port (video input)	No		
Serial programming speed	9600 – 38400 bps		
Functionality			
Vector graphics	Yes		
Dual driver capability	Yes		
Video input	No		
Data acquisition and trends	Yes		
		Ratings	
		Power supply voltage	24 V DC (18 to 30 V DC)
		Current consumption	Max 0.7 A at 24 VDC
		Fuse	Automatic
		Weight	Approx 2.3 Kg
		Environmental Conditions	
		Operating temperature	0 to 45 °C
		Storage temperature	-20 to +70 °C
		Operating and storage humidity	5 – 85 % RH non-condensing
		Protection class	IP65 (front panel)
		Dimensions	
		Faceplate LxH	287x232 mm (11.30x9.14")
		Cutout AxB	276x221 mm (10.87x8.70")
		Mounting depth (type 0050)	91 mm (3.58")
		Max panel thickness	5 mm (0.2")

Note 1: the lamp lifetime is the typical value for continuous operation at 25°C.

The product is designed for installation in industrial environments in compliance with the regulations:

Emitted interference EN 61000-6-4, 2001

Noise immunity EN 61000-6-2, 2001




Figure 1 – Cutout and front view

Ordering Information

eTOP32B-0050

9.6" VGA monochrome panel with touchscreen

Tn217

Ver. 1.00

Copyright © 2004 Sitek S.p.A. – Verona, Italy

Subject to change without notice

The information contained in this document is provided for informational purposes only. While efforts were made to verify the accuracy of the information contained in this documentation, it is provided "as is" without warranty of any kind.

www.exor-rd.com

AUDIN - 8, avenue de la malle - 51370 Saint Brice Courcelles

Tel : 03.26.04.20.21 - Fax : 03.26.04.28.20 - Web : <http://www.audin.fr> - Email : info@audin.fr

tn217-0.doc - 8.04.2005

UniOP eTOP32B