

# *ANT-DB1-RAF-RPSMA*

The ANT-DB1-RAF-RPSMA is a compact, dual-band, 1/2 wave antenna covering the 2.45 and 5.8GHz bands. The antenna features a tilt and swivel joint which allows it to be oriented at straight or right angles to the product or folded for storage and shipment. It attaches to the 702-W via an RP-SMA connector

#### 702-W APPLICATIONS

- Wireless LAN applications
- Client antennas
- 802.11b/g/n applications

#### **SPECIFICATIONS**

Band 1: 2.4Ghz Frequencies: Band 2: 5.8GHz

Gain @ 2.4GHz 2dBi Gain @ 5.8GHz 4dBi **VSWR:** < 2 50 ohms Impedance: Dimensions (Length x Diameter): 4.13" x 0.43"

104.9mm x 11mm

#### Range Estimates - 2.4GHz

Throughput	26Mbps	100Mbps
Distance (Miles)	1.35	0.12
Distance (kilometers)	2.18	.19
Tx Power	22dBm	15dBm
Receive Sensitivity	-91dBm	-77dBm
Number of Spacial Streams	2	2


### Range Estimates - 5.8GHz

Throughput	26Mbps	100Mbps
Distance (Miles)	0.81	0.07
Distance (kilometers)	1.30	.12
Tx Power	22dBm	15dBm
Receive Sensitivity	-90dBm	-76dBm
Number of Spacial Streams	2	2

\*Given the following parameters:

- Free Space loss / 2-ray ground reflection models
- Antenna is mounted directly nto an *N-TRON 702-W* Ethernet Radio mounted twenty-five (25) feet above ground level.
- Clear line of sight between radios with no obstructions of the first Fresnel Zone
- · 20MHz wide signal
- Center frequency = 2.452GHz or 5.805GHz
- 10dB loss assumed for weather conditions

Range estimates are theoretical. Actual results may vary based on installation conditions. A site survey should be performed as part of the planning process to determine the presence of RF interference and identify optimum installation



N-TRON USA & Corporate Headquarters 3101 International Blvd. Building 6 Mobile, AL 36606 • USA Phone +1-251-342-2164 Fax +1-251-342-6353

www.n-tron.com


® 2012 N-Tron Corporation. N-Tron and the N-Tron logo are trademarks of N-Tron Corporation. Product names mentioned herein are for identification purposes only and may be trademarks and/or registered trademarks of their respective company. Specifications subject to change without notice. The responsibility for the use and application of N-Tron products rests with the end user. N-Tron makes no warranties as to the fitness or suitability of any N-Tron product for any specific application. N-Tron Corporation shall not be liable for any damage resulting from the installation, use, or misuse of this product. Printed in USA. REV 2012.11.13




## QUALITY MANAGEMENT SYSTEM CERTIFIED BY DNV

=== ISO 9001:2008 ====


Azimuth Pattern: 2.4GHz




Azimuth Pattern: 5.8GHz




Elevation Pattern: 2.4GHz



Elevation Pattern: 5.8GHz



Elevation Side Pattern: 2.4GHz



Elevation Side Pattern: 5.8GHz

