

RAM[®] 9000 Industrial Cellular RTUs

Sixnet[®] Networking Series



▶▶▶ High-Density I/O RTUs with GPS and Local Control

Red Lion's Sixnet series RAM 9000 high-density I/O cellular RTUs with multi-carrier 4G LTE support provide advanced control and communication for monitoring and controlling remote assets and processes in extreme conditions.

RAM 9000 industrial cellular RTUs seamlessly connect Modbus and DNP3 enabled SCADA equipment via software selectable multi-carrier 4G LTE with fallback to 3G networks. Featuring a web-based event engine that can trigger built-in I/O or send SMS text messages based on real-time operational data, RAM cellular RTUs can perform advanced control at the edge and alert personnel of critical events. A built-in I/O concentrator allows the RAM to collect local sensor data from on-board I/O or external equipment and can optimize cellular bandwidth by optionally reporting only on an exception. With built-in Ethernet, serial, digital and analog I/O and GPS, RAM RTUs easily integrate with existing equipment enabling remote monitoring and control for M2M applications in industries including oil and gas, water/wastewater, utility, transportation and mining.



APPLICATIONS

- > Mining
- > Oil & Gas
- > Transportation
- > Utility
- > Water/Wastewater

PRODUCT HIGHLIGHTS

- > High-Performance Multi-Carrier 4G LTE Connectivity
- > Built-in I/O Lowers Total System Cost
- > Multiple Communication Ports
- > Active GPS Receiver Automatically Tracks Device Location
- > Routing Capabilities Provide Secure, Reliable Communication
- > Event Engine that can Send SMS Messages or Control I/O Based on Operational Data

FEATURES & BENEFITS

- > On-Board High-Density I/O
 - 2 digital inputs, 2 digital outputs, 3 analog inputs and 1 form c relay reduce the need for external I/O devices
 - Built-in I/O concentrator
- > Multiple Communication Ports
 - RS-232 and RS-485 provides seamless connectivity to remote devices
 - Native Modbus and DNP3 Support
- > Rugged, Industrial Design
 - Reliable operation in rugged environments
 - -40° to 75°C operating temperature*
- > IEEE802.11b/g/n Wi-Fi Compliant
 - Supports local client access to communicate with network assets
 - Configure and update firmware without physically connecting to RAM
- > Secure Ethernet Connectivity
 - Routing capabilities for reliable communication
 - Stateful firewall, SSL, GRE and VPN services and deep packet inspection reduce the risk of unwanted access
- > Advanced Event Engine Functionality
 - Easily configure control engine via drop-down menus
 - Trigger I/O, alarms and send SMS messages based on operational data

industrial
networking



RAM 9000 LTE Multi-Carrier Specifications

WIRELESS INTERFACE

AT&T LTE with fallback to HSPA+
 Bell Mobility LTE with fallback to HSPA+
 Generic LTE with fallback to HSPA+HS
 Rogers LTE with fallback to HSPA+
 TELUS LTE with fallback to HSPA+
 Verizon LTE with fallback to EVDO

PROGRAMMABLE PLATFORM

Configurable Events: up to 99 events can be triggered by I/O, Modbus registers, or over 200 system variable which in turn can send text messages or control I/O
 Software Development Kit (SDK)
 C/C++/Perl

PROTOCOL GATEWAY

I/O controller
 Modbus RTU/TCP/ASCII
 DNP3 Slave

SYSTEM PERFORMANCE

32-bit ARM9 400 MHz CPU
 512 MB NAND Memory
 128 MB RAM

TUNNELING

IPsec, GRE, OpenVPN

IP

NAT, port forwarding, dynamic DNS, DHCP
 Stateful inspection firewall, IP transparency

ROUTING PROTOCOLS

OSPF, BGP, RIP

CLUSTERING

VRRP

GPS

GNSS supported: GPS L1, GLONASS L1, Galileo E1
 high RF sensitivity plus jamming detection/removal

CONNECTORS

Ethernet: One (1) or five (5) 10/100Base-T RJ-45 ports
 WAN capability on port 2
 Serial: One (1) RS-232 (DB9) 115200bps
 One (1) RS-485 (screw block) 115200bps
 USB: One (1) USB 2.0 (mini)
 Antennas: Three (3) SMA connectors (antenna, diversity, GPS)
 One (1) RP-SMA connector (Wi-Fi optional)

INPUTS & OUTPUTS*

2 Digital Inputs
 2 Digital Outputs
 3 Analog Inputs
 1 Form C Relay

WI-FI INTERFACE (OPTIONAL)

Complies with IEEE802.11b/g/n
 Maximum output power up to 25dBm
 Supports up to 150Mbps with 40MHz channel

POWER INPUT

Range: 8-30 VDC (12 or 24 VDC nominal)
 Power consumption: (less DO power)
 Standby: 4W (all models)
 Transmitting:
 -9711: 5.0W – 9.4W (cellular only)
 -9731: 5.0W – 13.6W (cellular and Wi-Fi)
 Power consumption of DO: (max. each)
 30 W (1A at 30 VDC)
 Heat dissipation: 46 BTU/hour max

MECHANICAL

Dimensions: 132H x 127D x 70W mm (5.2" x 5.00" x 2.75")
 Material: Steel with black zinc coating
 Weight: 906 g (2 lbs)

ENVIRONMENTAL

Operating temperature: -40° to +75°C*
 Shock: IEC60068-2-27
 Vibration: IEC60068-2-6
 Humidity: 5 to 95% non-condensing
 Ingress: IP30 protection

CERTIFICATION

EMI/EMC:
 Emissions: FCC, Part 15 and Industry Canada, ICES-003; Class A; EN55022, IEC61000-6-4
 Immunity: IEC61000-6-2 (EN61000-4-2,3,4,5,6,8)
 Hazardous locations: Class I, Div. 2, Groups A, B, C, D, ISA 12.12.01
 Electrical safety: UL508/CSA22.2/14 (CUL); IEC61010-1
 Carrier specific approvals (Contact Red Lion for latest)
 RoHS compliant

WARRANTY

3 years on design and manufacturing defects

* See Hardware Manual for thermal considerations.

ORDERING GUIDE

MODEL NUMBER	SERIES	SERIAL		ETHERNET	WI-FI	CELLULAR	POWER CONNECTOR	DEFAULT CARRIERS**
		RS232	RS485	10/100				
RAM-9911-(Carrier Code)	RAM	1	1	2 (WAN/LAN)	N	4G LTE	DC powered	(AT) AT&T; (VZ) Verizon;
RAM-9931-(Carrier Code)	RAM	1	1	2 (WAN/LAN)	Y	4G LTE	DC powered	(AM) Generic* includes Bell Mobility, TELUS and Rogers

* See Band/Frequency table for compatibility



** Carrier that is pre-configured on device. Carrier can be selected via software.

FREQUENCY SPECIFICATIONS

TECHNOLOGY	BANDS	FREQUENCIES	ANTENNA CONFIGURATION
LTE	2, 4, 5, 13, 17, 25	700/850/1900 & 1700(AWS)/2100(AWS) MHz	MIMO Required
Fallback CDMA/EVDO	BC0, BC1, BC10	800/1900 MHz	Diversity Support
Fallback HSPA+	1, 2, 4, 5, 8	850/900/1900/2100 & 1700(AWS)/2100(AWS) MHz	Diversity Support
Fallback GSM/GPRS/EDGE	-	850/900/1800/1900 MHz	-

▶▶▶ RAM 9000 LTE Multi-Carrier Specifications

DIMENSIONS In inches (mm)



www.redlion.net

Connect. Monitor. Control.

Americas
sales@redlion.net

Asia-Pacific
asia@redlion.net

Europe
Middle East
Africa
europe@redlion.net

+1 (717) 767-6511

As the global experts in communication, monitoring and control for industrial automation and networking, Red Lion has been delivering innovative solutions for over forty years. Our automation, Ethernet and cellular M2M technology enables companies worldwide to gain real-time data visibility that drives productivity. Product brands include Red Lion, N-Tron® and Sixnet®. With headquarters in York, Pennsylvania, the company has offices across the Americas, Asia-Pacific and Europe. Red Lion is part of Spectris plc, the productivity-enhancing instrumentation and controls company. For more information, please visit www.redlion.net.

ADLD0384 062915 ©2015 Red Lion Controls, Inc. All rights reserved. Red Lion, the Red Lion logo, N-Tron and Sixnet are registered trademarks of Red Lion Controls, Inc. All other company and product names are trademarks of their respective owners.