

QUALITY MANAGEMENT SYSTEM CERTIFIED BY DNV

== ISO 9001:2008 ===

Ordering Information

108M12 Eight 10/100BaseTX Ports with M12 D-Coded Style Connectors, 10-30 VDC CAT5E-M12-M12-X Cat5E STP Cable with Straight M12 to Straight M12 Connector, Shielded CAT5E-M12-RJ45-X Cat5E STP Cable with Straight M12 to RJ-45 Connector, Shielded CAT5E-M12-X Cat5E STP Cable with Straight M12 Connector to bare end, Shielded CAT5E-RM12-M12-X Cat5E STP Cable with 90° M12 to Straight M12 Connector, Shielded Cat5E STP Cable with 90° M12 to 90° M12 Connector, Shielded CAT5E-RM12-RM12-X CAT5E-RM12-RJ45-X Cat5E STP Cable with 90° M12 to RJ-45 Connector, Shielded CAT5E-RM12-X Cat5E STP Cable with 90° M12 to bare end, Shielded

NTPS-24-1.3 DIN-Rail Power Supply 1.3A @24VDC

PWR-M12-A-X Power Cable, M12 A-Coded 90° Female Connector to bare end, Shielded PWR-RM12-A-X Power Cable, M12 A-Coded Straight Female Connector to bare end, Shielded

M12DRC-ISO DIN-Rail kit, two isolated plastic clips

M12DRC-MTL DIN-Rail kit, two metal clips

Where:

X = length of cable, fill in desired amount in feet. Ex: CAT5E-RM12-10 (for a 10ft cable)

