



LED lighting Kit made up of stabilized power PSU, anodized aluminum LED illuminator with 40° lens, chromium plated stainless steel gooseneck arm, aluminum anodized magnetic plate for fastening.

cod. LED: L40LED1W **IP40**

cod. PSU: A7LED1W **IP40**

ELECTRICAL FEATURES

Voltage	3,8 Vdc
Operating Current	250~350 mA dc
Power	1W
IEC class	II

MECHANICAL AND OPTICAL FEATURES

LED type	Cree XR-E
N. LED	1
LED lifetime	50000 h
Brightness	Narrow beam - 40° lens
Light colour	5300 °K
Spotlight LED	Ø25xL32,5mm
Arm	Ø6xL200mm
Magnetic plate	Ø30xH23mm
Fastening	Neodymium magnetic base
Switch	Embodied in PSU
Degree of protection	IP40
Colour	Aluminum

PSU FEATURES

Code	Vin	Vout	Iout	W	Size
A7LED1W	230 Vac	3,8 Vdc	250mA	3,5 W	90x55x50mm

ORDER CODES

L40LED1W	LED lamp
A7LED1W	PSU for L40LED1W

Flow light from working surface - H.1000mm

Ø (mm)	lux
100	820 lux
200	600 lux
300	450 lux
400	350 lux

Fastening

