SAFETY ACCESSORIES IGHT CURTAINS

\$DATALOGIC

DATALOGIC AUTOMATION

SG-LS SERIES

The LENS SHIELD accessory for safety light curtains, composed of a PMMA Altuglas plate that can be mounted on the front glass of the safety light, ensures an effective protection against dust, chips and incandescent drops, deriving from material working near the safety light curtain.

Thanks to the unique profile, available in different lengths, the accessory suits all the models of the SG2, SG4 and SE series.

The accessory can be easily installed thanks to the fixing brackets supplied in the package that exploit the side groove of the safety light curtain. It can also be quickly replaced when the glass is damaged.



HIGHLIGHTS

- PMMAAltuglas 3mm plate
- · Protects front glass of the light curtain from dust, chips and incandescent drops
- · One profile available in different lengths ideal for all models of the SG2, SG4 and SE series (150-1800mm)
- · Doesn't leave glue deposits or other residual material on the light curtain

APPLICATIONS

The SG-LS accessory is particularly suitable in working areas characterized by chips or incandescent drops deriving from material working or welding such as:

- · Punching machines
- Milling machines
- · Welding machines


Five plates are supplied in the package that supply adequate replacements even in presence of extremely high wear.

TECHNICAL DATA

Protected height*:	1501800mm				
	2, 3, 4 beams				
Housing material:	PMMA Altuglas				
Thickness	3 mm				
Reduction factor of the op.distance*:	10 % for each Lens Shield installed				
* technical data referred to safety light curtain where the accessory is mounted					

www.automation.datalogic.com AUDIN - 8, avenue de la malle - 51370 Saint Brice Courcelles - Tel : 03.26.04.20.21 - Fax : 03.26.04.28.20 - Web : http: www.audin.fr - Email : info@audin.fr

DIMENSIONS



	Measurement in mm								
	SG2, SG4B, SE Hand/Finger protection			SE Body protection					
	VERS.	L	Li	Lo	VERS.	L	Li	Lo	
	15	245	160	30	2r 050	642	490	75	
TS	30	392	345	45	3r 080	942	640	175	n°2+2 BRA- CKETS
К Н	45	540	400	60	4r 090	1042	660	200	
BRACKETS	60	686	520	75					오ᄪ고
	75	832	590	115					n°3+3 BRA- CKETS
n°2+2	90	980	640	175	4r 120	1342	480	200	
	105	1126	740	200		·	·	·	
IS	120	1274	445	200					
Ж	135	1422	520	200					
BRAG	150	1568	595	200	1				
n°3+3 BRACKETS	165	1715	670	200	1				
n°3	180	1860	745	200	1				

MODELS					
MODEL	DESCRIPTION	ORDER N°			
SG-LS 150	lens shield 150	95ASE1450			
SG-LS 300	lens shield 300	95ASE1460			
SG-LS 450	lens shield 450	95ASE1470			
SG-LS 600	lens shield 600	95ASE1480			
SG-LS 750	lens shield 750	95ASE1490			
SG-LS 900	lens shield 900	95ASE1500			
SG-LS 1050	lens shield 1050	95ASE1510			
SG-LS 1200	lens shield 1200	95ASE1520			
SG-LS 1350	lens shield 1350	95ASE1530			
SG-LS 1500	lens shield 1500	95ASE1540			
SG-LS 1650	lens shield 1650	95ASE1550			
SG-LS 1800	lens shield 1800	95ASE1560			
SG-LS 2	lens shield 2	95ASE1570			
SG-LS 3	lens shield 3	95ASE1580			
SG-LS 4-900	lens shield 4-900	95ASE1590			
SG-LS 4-120	lens shield 4-120	95ASE1600			
NOTE: Each package contains what is necessar	y to protect a single unit (TX or RX). To protect both	TX and RX, two pieces			

NOTE:Each package contains what is necessary to protect a single unit (1X or RX). To protect both 1X and RX, two pieces of the same code are needed

ACCESSORIES				
MODEL	DESCRIPTION	ORDER N°		
SG-LS-MC4	Elastic fastner for LENS SHIELD (kit 4pcs.)	95ASE1810		



The company endeavours to continuously improve and renew its products; for this reason the technical data and contents of this catalogue may undergo variations without prior notice. For correct installation and use, the company can guarantee only the data indicated in the instruction manual supplied with the products.



www.automation.datalogic.com