


Position Switches



More than safety.



EUCHNER

More than safety.



Emil Euchner, the company's founder and inventor of the multiple limit switch, circa 1928.



Around the world – the Swabian specialists in motion sequence control for mechanical and systems engineering.

EUCHNER's history began in 1940 with the establishment of an engineering office by Emil Euchner. Since that time, EUCHNER has been involved in the design and development of switchgear for controlling a wide variety of motion sequences in mechanical and systems engineering. In 1953, Emil Euchner founded EUCHNER + Co., a milestone in the company's history. In 1952, he developed the first multiple limit switch – to this day a symbol of the enterprising spirit of this family-owned company.

Automation – Safety – ManMachine

Today, our products range from electromechanical and electronic components to complex system solutions. With this wide range of products we can provide the necessary technologies to offer the right solution for special requirements – regardless of whether these relate to reliable and precise positioning or to components and systems for safety engineering in the automation sector.

EUCHNER products are sold through a world-wide sales network of competent partners. With our closeness to the customer and the guarantee of reliable solutions throughout the globe, we enjoy the confidence of customers all over the world.

Quality, reliability, precision

Quality, reliability and precision are the hallmarks of our corporate philosophy. They represent concepts and values to which we feel totally committed.

At EUCHNER, quality means that all our employees take personal responsibility for the company as a whole and, in particular, for their own field of work. This individual commitment to perfection results in products which are ideally tailored to the customers' needs and the requirements of the market. After all: our customers and their needs are the focus of all our efforts. Through efficient and effective use of resources, the promotion of personal initiative and courage in finding unusual solutions to the benefit of our customers, we ensure a high level of customer satisfaction. We familiarize ourselves with their needs, requirements and products and we learn from the experiences of our customers' own customers.

EUCHNER – More than safety.



Quality – made by EUCHNER

Position Switches



General Information	4
Precision Single Hole Fixing Limit Switches	9
With reed contact	10
With snap-action switching element	14
With slow-action switching element	21
Multiple clamping strip for precision single hole fixing limit switches M12 x 1	22
Precision Single Limit Switches	23
Design N01	24
Design NB01	27
Design SN01	27
Design N1A	29
Design N10	32
Design N11	33
Inductive Single Limit Switches	35
Design ENA	36
Design ESN	38
Accessories	42
Round connectors	42
LED function display	44
Cable glands	44
Additional products	44
Appendix	45
Terms and explanations	45
Item Index	47
Product Guide	49

Position Switches

EUCHNER

General Information

Precision single hole fixing limit switches with reed contact or snap-action switching element

EUCHNER precision single hole fixing limit switches are technically sophisticated control switches which have been proving their reliability, day in and day out, for decades in harsh industrial applications.

These mechanically actuated precision single hole fixing limit switches are IP 67 rated and are entirely maintenance-free.

EUCHNER precision single hole fixing limit switches feature a thread on the upper part and can thus be inserted or screwed through the mounting hole either from the cable end or from the actuator end. Setting the position of the operating point opposite the part of the machine to be sensed is easy with this thread.

The compact overall size and the round type of construction allow installation directly at the sensing points. This feature dispenses with the complicated levers or linkages associated with a high level of design complexity and expense.




Precision single limit switches

EUCHNER precision single limit switches are technically precise control switches which have been developed on the basis of practical requirements in close collaboration with machine tool manufacturers.

The use of high-quality materials, the interplay of sophisticated technology and practically oriented design guarantee operation under even the toughest conditions.

EUCHNER precision single limit switches are used for positioning and controlling machines and in industrial installations.

The different designs, with a choice of five different types of plunger, and easy adjustability from longitudinal to transverse actuation offer the user a broad range of individual possible applications.




Inductive single limit switches

Inductive single limit switches are used for positioning and control in all areas of mechanical and systems engineering and systems engineering such as for automation tasks in the wood, textile and plastic industry.

Due to their non-contact and thus wear-free principle of operation, inductive single limit switches are insensitive to heavy vibration, heavy soiling and have an above average mechanical life even in aggressive ambient conditions.

Interchangeability with mechanical single limit switches means that it is possible to straightforwardly modify machines. The switches can therefore be retrofitted on existing machine installations to take full advantage of the benefits of non-contact switches.




Position Switches

Switching Elements with Reed Contact

Reed contact


The reed contact comprises two ferromagnetic contacts in a glass bulb. When the reed contact is placed in a magnetic field, the contacts adopt opposite polarities and are closed.
For series EGT with reed contact.



Mechanical Switching Elements


Changeover contact with snap-action function

Snap-action switching element ¹⁾ with single gap and three connections.
For series EGT with snap-action switch and series N01, NB01, SN01 with soldered connection.




Snap-action switching element ¹⁾ with one NO contact and one NC contact

With double gap and electrically isolated switching bridge. The two moving contacts are electrically isolated from each other. Switching element with four connections.
For series SN01 with soldered connection and series N1A, N10, N11.




Safety switching element with slow-action switching contact ²⁾

With one positively driven NC contact and double gap. Switching contact with two connections.
For use in single limit switches with safety function.
For series NB01 with safety function and series N1A with safety function.



Safety switching element with snap-action switching contact ¹⁾

With one positively driven NC contact and one NO contact. Double gap and electrically isolated switching bridge. Switching contact with four connections.
For use in single limit switches with safety function.
For series N1A with safety function.



1) A snap-action switching element has a switching contact which opens or closes regardless of the approach speed during actuation.
2) A slow-action switching element has a switching contact which opens and closes depending on the approach speed during actuation.

Position Switches

Positively driven contacts

Positively driven contacts are used in some switching elements. These are special switching contacts that are designed to ensure the switching contacts are always reliably separated. Even if contacts are welded together, the connection is opened by the actuating force.

It is a common feature of all switching elements that at least one switching contact is designed as a positively driven contact. Often two positively driven contacts are employed to increase safety using the principle of duplicated design (redundancy). This dual-channel design ensures that on the failure of one channel or on a fault in the control circuit (e. g. in the machine wiring), the interlocking can still be provided with the aid of the second channel.




Positively driven position switch.

Safety switching elements marked with this symbol are not available as replacement switching elements.

Inductive Switching Elements

NO function


The NO function means that the load current flows when the active face of the inductive switching element is activated and that no current flows when the active face is not activated.



DC NO, PNP

NC function

The NC function means that the load current does not flow when the active face of the inductive switching element is activated and that current flows when the active face is not activated.




DC NC, PNP

NO + NC function

The NO + NC function incorporates both an NO function and an NC function.

Associated circuit diagrams and wiring diagrams are given in the technical data.



DC NO + NC, PNP

Position Switches

EUCHNER


Precision Single Limit Switches

Design

The die-cast aluminum housings for the EUCHNER single limit switches have been proven in even the harshest conditions with their high strength and resistance to corrosion.

They do not require a protective paint finish, but can be painted at any time without prior treatment.

Depending on the design, the hardened plungers made of stainless steel run precisely in either the anodic oxidized guide bore in the housing or in a sintered bronze sleeve. These maintenance-free sliding elements make a key contribution to the reliability and correct operation of the switches. Even beyond the guaranteed mechanical life.




Exterior diaphragm

To provide protection against resinous cooling lubricants and against the penetration of very small particles, e. g. saw dust, graphite and glass dust, a series with an exterior diaphragm is available.

The exterior diaphragm provides additional sealing of the plunger outside the housing.


The plunger guides in the housing are thus reliably protected from the penetration of the cooling lubricant. Plunger sticking is prevented and the replacement of the switch or plunger is unnecessary. For technical data on this series see page 31.



Seals

EUCHNER uses the high-quality and proven acrylonitrile-butadiene rubber (NBR) for all seals and sealed areas. This material is resistant to oils, greases, fuels, hydraulic fluids and most known cooling lubricants. Moreover, NBR possesses high mechanical rigidity over a wide temperature range and so it is perfectly suitable for the highly stressed diaphragm seal, which separates the plunger compartment and the interior of the switch.

The material of the diaphragm seal is a key criterion for the quality, mechanical life and precision of the EUCHNER precision single limit switches. The same material is used for the cover seal and the cable entry.




Position Switches

EUCHNER

Adjustability


On the chisel plungers and the roller plungers (normal and extended) the approach direction can be changed by 90° at any time. After unscrewing the locking pin, the plunger can be rotated by 90°.



LED function display


If required, the EUCHNER single limit switches of design N1A can be equipped with an LED function display (AC/DC 10 - 60 V or AC 110/230 V, color red).

Built-in electronic regulation ensures that the luminosity remains constant independent of the voltage applied.



Cable connection

EUCHNER position switches are tested to degree of protection IP 67 in accordance with IEC 60529. In order to obtain this degree of protection, only high-quality metal cable glands with a captive sealing ring are used. A selection for different cable diameters is listed on page 44.



Single Hole Fixing Limit Switches - Cylindrical Design

The round design with simple, single-hole assembly allows installation of the controls directly at the scanning points. Exact adjustment is permitted by means of the precision metric thread. The limit switches with inert gas contact (reed contact) can be operated up to a water column pressure of 30 meters with degree of protection IP 68.

Features

- ▶ 6 basic types M12 x 1 to M18 x 1.5
- ▶ Housing of nickel-plated brass or stainless steel
- ▶ Mechanical life up to 30 million operating cycles
- ▶ Degree of protection IP 68 / IP 67
- ▶ Switching point accuracy ± 0.01 max.
- ▶ With hard-wired cable or with M 12 plug connection



Position Switches



Precision single hole fixing limit switches





- ▶ With reed contact and protective diode
- ▶ Plunger material stainless steel
- ▶ Any installation position

Design EGT12, M12 x 1, dome plunger
Connection cable, double insulated

Design EGT12, M12 x 1, dome plunger
Plug connector M12 with PE connection





Dimension drawings



⚠ Never switch incandescent lamps. Not even for test purposes.
Single hole fixing limit switches must not be used as an end stop.

Wiring diagrams



Technical data

Housing material	Sleeve	Plastic	Brass, nickel-plated
	Threaded section	Stainless steel	Stainless steel
Degree of protection according to IEC 60529		IP 68	IP 67 Mating connector inserted and screwed tight
Ambient temperature	[°C]	-25 ¹⁾ ...+80	-25...+80
Approach speed, max.	[m/min]	8	8
Mechanical life	axial actuation	30 x 10 ⁶ operating cycles	30 x 10 ⁶ operating cycles
	radial actuation	1 x 10 ⁶ operating cycles (dog 30°)	1 x 10 ⁶ operating cycles (dog 30°)
Operating point accuracy ²⁾	[mm]	± 0.01	± 0.01
Actuating force (end position)	[N]	Approx. 16	Approx. 16
Switching element		Reed contact	Reed contact
Switching contact		1 NO contact or 1 NC contact	1 NO contact or 1 NC contact
Contact material		Rhodium	Rhodium
Rated insulation voltage U _i	[V]	50	50
Utilization category acc. to IEC 60947-5-1		AC-12 U _e 30 V I _e 0.3 A DC-13 U _e 24 V I _e 0.3 A	AC-12 U _e 30 V I _e 0.3 A DC-13 U _e 24 V I _e 0.3 A
Switching current, min., at 24 V	[mA]	1	1
Switching voltage, min.	[V DC]	1	1
Short circuit protection (control circuit fuse)	[A gG]	0.4	0.4
Connection type		PUR cable 2 x 0.5 mm ²	Plug connector M12 ³⁾

1) Cable hard wired.

2) The reproducible operating point accuracy relates to axial actuation, after run-in of approx. 2000 operating cycles.

3) For mating connector see page 42 and 43.

Ordering table

1 NO contact	Connection cable 2 m	On request	-
	Connection cable 5 m	082 201 EGT12A5000	-
	Plug connector	-	075 426 EGT12ASFM5
1 NC contact	Connection cable 2 m	On request	-
	Connection cable 5 m	078 848 EGT12R5000	-
	Plug connector	-	075 427 EGT12RSFM5

Position Switches






Design EGT12, M12 x 1, dome plunger
Plug connector M12, long plunger




Design EGT11, M14 x 1, ball plunger
Plug connector M12 with PE connection

Design EGT12, M12 x 1, roller plunger
Plug connector M12, double insulated

Dimension drawings



Wiring diagrams



Brass, nickel-plated	Brass, nickel-plated	Brass, nickel-plated
Stainless steel	Stainless steel	Stainless steel
IP 67	IP 67	IP 67
Mating connector inserted and screwed tight	Mating connector inserted and screwed tight	Mating connector inserted and screwed tight
-25...+80	-25...+80	-25...+80
5	60	20
5 x 10 ⁶ operating cycles	30 x 10 ⁶ operating cycles	30 x 10 ⁶ operating cycles
± 0.01	5 x 10 ⁶ operating cycles (dog 15°)	± 0.01
Approx. 16	± 0.01	Approx. 16
Reed contact	Approx. 3	Reed contact
1 NO contact or 1 NC contact	Reed contact	1 NO contact or 1 NC contact
Rhodium	1 NO contact or 1 NC contact	Rhodium
50	Rhodium	50
AC-12 U _e 30 V I _e 0.3 A	50	AC-12 U _e 30 V I _e 0.3 A
DC-13 U _e 24 V I _e 0.3 A	50	DC-13 U _e 24 V I _e 0.3 A
1	1	1
1	1	1
0.4	0.4	0.4
Plug connector M12 ³⁾	Plug connector M12 ³⁾	Plug connector M12 ³⁾

-	-	-
-	-	-
095 112 EGT12ASF5C2083	093 352 EGT11A2NSFM5	078 483 EGT12ARSEM4C1888
-	-	-
-	-	-
-	091 848 EGT11R2NSFM5	079 139 EGT12RRSEM4C1888



Position Switches



Precision single hole fixing limit switches

- ▶ With reed contact
- ▶ Plunger material stainless steel
- ▶ Any installation position



For mating connector with LED display





Design EGT1/4, M14 x 1, ball plunger
Connection cable, double insulated/plug connector M12

Design EGT1/4, M14 x 1, ball plunger
Plug connector M12





Dimension drawings



⚠ Never switch incandescent lamps. Not even for test purposes.
Single hole fixing limit switches must not be used as an end stop.

Wiring diagrams



Technical data

Housing material	Sleeve	Plastic	Brass, nickel-plated	Brass, nickel-plated
	Threaded section	Stainless steel		Stainless steel
Degree of protection according to IEC 60529		IP 68	IP 67 ⁴⁾	IP 67 Mating connector inserted and screwed tight
Ambient temperature	[°C]	-25 ¹⁾ ...+80	-25...+80	-25...+80
Approach speed max.	[m/min]	8		8
Mechanical life (axial)		30 x 10 ⁶ operating cycles		30 x 10 ⁶ operating cycles
Operating point accuracy ²⁾	[mm]	± 0.01		± 0.01
Actuating force (end position)	[N]	Approx. 16 / 3 on request		Approx. 16 / 3 on request
Switching element		Reed contact		Reed contact
Switching contact		1 NO contact or 1 NC contact		1 NO contact or 1 NC contact
Contact material		Rhodium		Rhodium
Rated insulation voltage U _i	[V]	250 □	50	50
Utilization category	AC-12	U _e 230 V I _e 0.03 A	U _e 30 V I _e 0.3 A	AC-12 U _e 30 V I _e 0.3 A
acc. to IEC 60947-5-1	DC-13	U _e 24 V I _e 0.3 A	U _e 24 V I _e 0.3 A	DC-13 U _e 24 V I _e 0.3 A
Switching current, min., at 24 V	[mA]	1		1
Switching voltage, min.	[V DC]	1		1
Short circuit protection (control circuit fuse)	[A gG]	0.4		0.4
Connection type		PUR cable 2 x 0.5 mm ² , Encapsulated	Plug connector M12 ³⁾	Plug connector M12 ³⁾

1) Cable hard wired.

2) The reproducible operating point accuracy relates to axial actuation, after run-in of approx. 2000 operating cycles.

3) For mating connector see page 42 and 43.

4) Mating connector inserted and screwed tight.

Ordering table

1 NO contact	Connection cable 2 m	001 366 ⁵⁾ EGT1/4A2000	-
	Connection cable 5 m	001 368 ⁵⁾ EGT1/4A5000	-
	Plug connector	033 976 EGT1/4ASEM4	075 644 EGT1/4ASEM4C1802
1 NC contact	Connection cable 2 m	001 371 ⁵⁾ EGT1/4R2000	-
	Connection cable 5 m	001 372 ⁵⁾ EGT1/4R5000	-
	Plug connector	033 982 EGT1/4RSEM4	-

5) No UL approval. UL approval only for single hole fixing limit switch with plug connector

Position Switches



Made of high-quality stainless steel



With scraper made of PU



With scraper made of PU






Design EGT1/4, M14 x 1, ball plunger
Connection cable, max. pressure 300 kPa



Design EGT1/4, M14 x 1, ball plunger
Plug connector M12

Design EGT1/4, M14 x 1, dome plunger
Plug connector M12

Dimension drawings



Wiring diagrams



High-quality stainless steel	Brass, nickel-plated Stainless steel	Brass, nickel-plated Stainless steel
IP 68	IP 67	IP 67
-25...+80	Mating connector inserted and screwed tight -25...+80	Mating connector inserted and screwed tight -25...+80
8	Approx. 16	8
30 x 10 ⁶ operating cycles ± 0.01	5 x 10 ⁶ operating cycles ± 0.01	30 x 10 ⁶ operating cycles ± 0.01
Approx. 16	Approx. 16	Approx. 16
Reed contact	Reed contact	Reed contact
1 NO contact	1 NO contact or 1 NC contact	1 NO contact
Rhodium	Rhodium	Rhodium
50	50	50
AC-12 U _e 30 V I _e 0.3 A	AC-12 U _e 30 V I _e 0.3 A	AC-12 U _e 30 V I _e 0.3 A
DC-13 U _e 24 V I _e 0.3 A	DC-13 U _e 24 V I _e 0.3 A	DC-13 U _e 24 V I _e 0.3 A
1	1	1
1	1	1
0.4	0.4	0.4
Hydrofirm cable 2x0.5 mm ² , encapsulated	Plug connector M12 ³⁾	Plug connector M12 ³⁾

094 982 EGT1/4A2000C2079	-	102 476 EGT1/4A2000C2137
-	-	-
-	095 278 EGT1/4ASEM4C2088	098 071 EGT1/4ASEM4C2137
-	-	-
-	-	-
-	104 316 EGT1/4RSEM4C2088	104 372 EGT1/4RSEM4C2137



Position Switches



Precision single hole fixing limit switches





- ▶ With snap-action switching element
- ▶ Plunger material stainless steel
- ▶ Any installation position

Design EGM12, M12 x 1, flat plunger
Connection cable, double insulated

Design EGM12, M12 x 1, flat plunger
Plug connector M12






Dimension drawings



⚠ Single hole fixing limit switches must not be used as an end stop.

Wiring diagrams



Technical data

	Stainless steel		Stainless steel	
	IP 65		IP 65	
Housing material	Stainless steel		Stainless steel	
Degree of protection according to IEC 60529	IP 65		IP 65	
Ambient temperature [°C]	-20 ¹⁾ ...+80	-30...+80	-20 ¹⁾ ...+80	-30...+85
Approach speed max. [m/min]	8		8	
Mechanical life (axial)	1 x 10 ⁶ operating cycles		1 x 10 ⁶ operating cycles	
Operating point accuracy ²⁾ [mm]	± 0.01		± 0.01	
Actuating force (end position) [N]	Approx. 16		Approx. 16	
Switching element	Snap-action switching contact		Snap-action switching contact	
Switching contact	1 changeover contact		1 changeover contact	
Contact material	Silver alloy, gold-plated		Silver alloy, gold-plated	
Rated insulation voltage U _i [V]	250		50	
Rated impulse withstand voltage U _{imp} [kV]	2.5		1.5	
Utilization category acc. to IEC 60947-5-1	AC-15 U _e 230 V I _e 0.5 A DC-13 U _e 24 V I _e 0.6 A		AC-15 U _e 50 V I _e 0.5 A DC-13 U _e 24 V I _e 0.6 A	
Switching current, min., at 24 V [mA]	10		10	
Switching voltage, min. [V DC]	12		12	
Short circuit protection (control circuit fuse) [A gG]	2		2	
Connection type	PUR cable 3x0.5 mm ²	Silicone cable 3x0.5 mm ²	Plug connector M12 ³⁾	

1) Cable hard wired.

2) The reproducible operating point accuracy relates to axial actuation, after run-in of approx. 2000 operating cycles.

3) For mating connector see page 42 and 43.

Ordering table

	075 556		076 464	
	EGM12-1200C1791		EGM12-1200C1820	
1 changeover contact	Connection cable 1.2 m	075 556	076 464	-
	Connection cable 2 m	-	-	-
	Connection cable 4 m	076 154	-	-
	Connection cable 5 m	-	-	-
Plug connector	-	-	082 205	093 733
			EGM12SEM4	EGM12SEM4C1820


Position Switches

EUCHNER




Design EGM12, M12 x 1, flat plunger
Plug connector M8



Dimension drawings





Wiring diagrams



Design EGT1, M12 x 1, ball plunger
Connection cable with PE connection



Design EGT1, M12 x 1, ball plunger
Plug connector M12



Stainless steel	Brass, nickel-plated	Brass, nickel-plated
IP 65	IP 67	IP 67
Mating connector inserted and screwed tight	Mating connector inserted and screwed tight	Mating connector inserted and screwed tight
-20...+85	-25 ¹⁾ ...+80	-25...+80
8	8	8
1 x 10 ⁶ operating cycles	1 x 10 ⁶ operating cycles	1 x 10 ⁶ operating cycles
± 0.01	± 0.01	± 0.01
Approx. 16	Approx. 20	Approx. 20
Snap-action switching contact	Snap-action switching contact	Snap-action switching contact
1 NO contact	1 changeover contact	1 changeover contact
Silver alloy, gold-plated	Silver alloy, gold-plated	Silver alloy, gold-plated
50	250	50
1.5	2.5	2.5
AC-15 U _e 24 V I _e 0.5 A	AC-15 U _e 230 V I _e 0.5 A	AC-15 U _e 50 V I _e 0.5 A
DC-13 U _e 24 V I _e 0.6 A	DC-13 U _e 24 V I _e 0.6 A	DC-13 U _e 24 V I _e 0.6 A
10	10	10
12	12	12
2	2	2
Plug connector M8 ³⁾	PUR cable 4 x 0.5 mm ²	Plug connector M12 ³⁾

-	-	-
-	092 695 EGT1M12-2000	-
-	-	-
-	093 364 EGT1M12-5000	-
077 228 EGM12SAM3C1868	-	093 365 EGT1M12SEM4



Position Switches



Precision single hole fixing limit switches





- ▶ With snap-action switching element
- ▶ Plunger material stainless steel
- ▶ Any installation position

Design EGT1, M14 x 1, ball plunger
Connection cable with PE connection

Design EGT1, M14 x 1, ball plunger
Plug connector M12





Dimension drawings



⚠ Single hole fixing limit switches must not be used as an end stop.

Wiring diagrams



Technical data

	Design EGT1, M14 x 1, ball plunger Connection cable with PE connection	Design EGT1, M14 x 1, ball plunger Plug connector M12
Housing material	Brass, nickel-plated	Brass, nickel-plated
Degree of protection according to IEC 60529	IP 67	IP 67 Mating connector inserted and screwed tight
Ambient temperature [°C]	-25 ¹⁾ ...+80	-25...+80
Approach speed, max. [m/min]	8	8
Mechanical life (axial)	1 x 10 ⁶ operating cycles	1 x 10 ⁶ operating cycles
Operating point accuracy ²⁾ [mm]	± 0.01	± 0.01
Actuating force (end position) [N]	Approx. 20	Approx. 20
Switching element	Snap-action switching contact	Snap-action switching contact
Switching contact	1 changeover contact	1 changeover contact
Contact material	Silver alloy, gold-plated	Silver alloy, gold-plated
Rated insulation voltage U _i [V]	250	50
Rated impulse withstand voltage U _{imp} [kV]	2.5	2.5
Utilization category acc. to IEC 60947-5-1	AC-15 U _e 230 V I _e 0.5 A DC-13 U _e 24 V I _e 0.6 A	AC-15 U _e 50 V I _e 0.5 A DC-13 U _e 24 V I _e 0.6 A
Switching current, min., at 24 V [mA]	10	10
Switching voltage, min. [V DC]	12	12
Short circuit protection (control circuit fuse) [A gG]	2	2
Connection type	PUR cable 4 x 0.5 mm ²	Plug connector M12 ³⁾

1) Cable hard wired.

2) The reproducible operating point accuracy relates to axial actuation, after run-in of approx. 2000 operating cycles.

3) For mating connector see page 42 and 43.

Ordering table

Ordering code	Description	Part number	Notes
1 changeover contact	Connection cable 2 m	001 732 EGT1-2000	-
	Connection cable 5 m	001 733 EGT1-5000	-
	Plug connector	-	019 727 EGT1SEM4

Position Switches

EUCHNER

For plug connector with LED display





Suitable for aggressive coolants, Diaphragm made out of Viton





Design EGT1, M14 x 1, ball plunger
Plug connector M12

Design EGT1, M14 x 1, ball plunger
Plug connector M12

Dimension drawings



Wiring diagrams



Brass, nickel-plated	Brass, nickel-plated
IP 67	IP 67
Mating connector inserted and screwed tight	Mating connector inserted and screwed tight
-25...+80	-5...+80
8	8
1 x 10 ⁶ operating cycles	1 x 10 ⁶ operating cycles
± 0.01	± 0.01
Approx. 20	Approx. 20
Snap-action switching contact	Snap-action switching contact
1 changeover contact	1 changeover contact
Silver alloy, gold-plated	Silver alloy, gold-plated
50	50
2.5	2.5
DC-13 U _e 24 V I _e 0.6 A	AC-15 U _e 50 V I _e 0.5 A DC-13 U _e 24 V I _e 0.6 A
10	10
12	12
2	2
Plug connector M12 ³⁾	Plug connector M12 ³⁾

-	-
-	-
054 250 EGT1SEM4C1613	077 347 EGT1SEM4C1832



Position Switches



Precision single hole fixing limit switches





- ▶ With snap-action switching element
- ▶ Plunger material stainless steel
- ▶ Any installation position

Design EGT2, M18 x 1.5, ball plunger
Connection cable with PE connection

Design EGT2, M18 x 1.5, ball plunger
Plug connector M12





Dimension drawings



⚠ Single hole fixing limit switches must not be used as an end stop.

Wiring diagrams



Technical data

	Brass, nickel-plated	Brass chromium plated
Housing material	Brass, nickel-plated	Brass chromium plated
Degree of protection according to IEC 60529	IP 67	IP 67
Ambient temperature [°C]	-5...+60	-5...+60
Approach speed, max. [m/min]	10	10
Mechanical life	3 x 10 ⁶ operating cycles	3 x 10 ⁶ operating cycles
Operating point accuracy ¹⁾ [mm]	± 0.01	± 0.01
Actuating force (end position) [N]	Approx. 24	Approx. 24
Switching element	Snap-action switching contact	Snap-action switching contact
Switching contact	1 NC contact and 1 NO contact	1 NC contact and 1 NO contact
Contact material	Fine silver gold-plated	Fine silver gold-plated
Rated insulation voltage U _i [V]	250	50
Rated impulse withstand voltage U _{imp} [kV]	2.5	2.5
Utilization category acc. to IEC 60947-5-1	AC-15 U _e 230 V I _e 2 A DC-13 U _e 24 V I _e 1 A	AC-15 U _e 30 V I _e 2 A DC-13 U _e 24 V I _e 1 A
Switching current, min., at 24 V [mA]	10	10
Switching voltage, min. [V DC]	12	12
Short circuit protection (control circuit fuse) [A gG]	2	2
Connection type	PUR cable 5 x 0.75 mm ²	Plug connector M12 ²⁾

1) The reproducible operating point accuracy relates to axial actuation, after run-in of approx. 2000 operating cycles.
2) For mating connector see page 42 and 43.

Ordering table

1 NC contact + 1 NO contact	Connection cable 2 m	001 864 EGT2-2000	-
	Connection cable 5 m	001 865 EGT2-5000	-
	Plug connector	-	052 504 EGT2SEM4

Position Switches

EUCHNER



Switch head can be used as end stop



Switch head can be used as end stop






Design EGT2, M18 x 1.5, ball plunger
Plug connector M12 with PE connection




Design EGT3, Ø 18, ball plunger
Connection cable with PE connection

Design EGT3, Ø 18, ball plunger
Plug connector M12

Dimension drawings



Wiring diagrams



Brass chromium plated	Steel/brass	Steel/brass
IP 67	IP 67	IP 67
Mating connector inserted and screwed tight		
-5...+60	-5...+60	-5...+60
10	Contact force max. 40 kN	Contact force max. 40 kN
3 x 10 ⁶ operating cycles	3 x 10 ⁶ operating cycles	3 x 10 ⁶ operating cycles
± 0.01	± 0.01	± 0.01
Approx. 24	Approx. 18	Approx. 18
Snap-action switching contact	Snap-action switching contact	Snap-action switching contact
1 NC contact and 1 NO contact	1 NC contact and 1 NO contact	1 NC contact and 1 NO contact
Fine silver gold-plated	Fine silver gold-plated	Fine silver gold-plated
50	250	50
2.5	2.5	2.5
AC-15 U _e 30 V I _e 2 A	AC-15 U _e 230 V I _e 2 A	AC-15 U _e 30 V I _e 2 A
DC-13 U _e 24 V I _e 1 A	DC-13 U _e 24 V I _e 1 A	DC-13 U _e 24 V I _e 1 A
10	10	10
12	12	12
2	2	2
Plug connector M12 ²⁾	PUR cable 5 x 0.75 mm ²	Plug connector M12 ²⁾

-	001 896 EGT3-2000	-
-	001 897 EGT3-5000	-
042 819 EGT2SEM5	-	070 834 EGT3SEM4

Position Switches

EUCHNER

Precision single hole fixing limit switches

With 4 switching contacts




- ▶ With snap-action switching element
- ▶ Plunger material stainless steel
- ▶ Any installation position

Design EGT4, M18 x 1.5, ball plunger
Connection cable with PE connection




Dimension drawings



⚠ Single hole fixing limit switches must not be used as an end stop.

Wiring diagrams



Technical data

Housing material	Brass, nickel-plated
Degree of protection according to IEC 60529	IP 67
Ambient temperature [°C]	-25 ¹⁾ ...+70
Approach speed, max. [m/min]	10
Mechanical life	5 x 10 ⁵ operating cycles
Operating point accuracy ²⁾ [mm]	± 0.01
Actuating force (end position) [N]	Approx. 25
Switching element	Snap-action switching contact
Switching contact	2 NC contacts and 2 NO contacts
Contact material	Fine silver gold-plated
Rated insulation voltage U _i [V]	250
Rated impulse withstand voltage U _{imp} [kV]	2.5
Utilization category acc. to IEC 60947-5-1	AC-15 U _e 230 V I _e 2 A DC-13 U _e 24 V I _e 1 A
Switching current, min., at 24 V [mA]	10
Switching voltage, min. [V DC]	12
Short circuit protection (control circuit fuse) [A gG]	2
Connection type	PUR cable 9 x 0.5 mm ²

1) Cable hard wired.

2) The reproducible operating point accuracy relates to axial actuation, after run-in of approx. 2000 operating cycles.

Ordering table

1 NC contact + 1 NO contact	Connection cable 2 m	094 339 EGT4-2000
	Connection cable 5 m	092 026 EGT4-5000
	Connection cable 10 m	093 967 EGT4-10000

Position Switches

EUCHNER

Precision single hole fixing limit switches

- ▶ With slow-action switching element
- ▶ Plunger and housing made of high-quality stainless steel
- ▶ Any installation position
- ▶ Threaded section M12 x 1


Switching element, with 3 switching contacts



Design EGZ12, M12 x 1, dome plunger
Connection cable with PE connection



Dimension drawings



⚠ Single hole fixing limit switches must not be used as an end stop.

Wiring diagrams



Technical data

Housing material	Stainless steel	
Plunger material	Stainless steel 60 HRC hardened and polish-ground	
Degree of protection according to IEC 60529	IP 67	
Ambient temperature	[°C]	-20 ¹⁾ ...+80
Approach speed, max.	[m/min]	8
Mechanical life	3 x 10 ⁶ operating cycles	
Actuating force at 20 °C	[N]	< 16
Switching element	Slow-action switching contact	
Switching contact	See travel diagram	
Contact material	Silver alloy, gold flashed	
Rated insulation voltage U _i	[V]	250
Rated impulse withstand voltage U _{imp}	[kV]	2.5
Utilization category according to EN 60947-1-5	AC-15 U _e 230 V I _e 4 A DC-13 U _e 24 V I _e 4 A	
Switching current, min., at 24 V	[mA]	1
Switching voltage, min., at 10 mA	[V DC]	12
Short circuit protection (control circuit fuse)	[A gG]	4
Connection type	PUR cable 7 x 0.5 mm ²	

1) Cable hard wired.

Ordering table

Connection cable	ES12	ES03
Connection cable 5 m	094 823 ²⁾ EGZ12-12-5000	On request

2) UL approval pending




Position Switches



Multiple clamping strip


- ▶ For single hole limit switch with threaded section M12 x 1
- ▶ Switch position as for multiple limit switches in accordance with DIN 43697
- ▶ For 2, 4 or 6 single hole fixing limit switches



The multiple clamping strip is used for mounting several single hole fixing limit switches of design EGT 12 / EGM 12. The robust actuator-sensor bracket with quick-action fastening system is mounted on an aluminum flange with fastening holes in accordance with DIN 43697.

Spacing 12 mm

Dimension drawings



Ordering table


Item	Number of brackets	Dimension l ₁ [mm]	Order No.
RGKB02N12	2	62	084 511
RGKB04N12	4	86	084 514
RGKB06N12	6	110	084 510

Precision Single Limit Switches

These switches are used in mechanical and systems engineering for controlling and positioning tasks. The robust housings made of die-cast anodized aluminum are characterized by their high level of mechanical endurance and corrosion resistance.

Features

- ▶ 9 basic types in die-cast aluminum casing
- ▶ From the miniature version 40 x 40 mm to the standard size according to DIN 43693
- ▶ Mechanical life up to 30 million operating cycles
- ▶ Designs with safety function for mechanical and personal protection
- ▶ 4 different plunger types
- ▶ Cable entry or M12 plug connection



Position Switches



Precision single limit switches



For temperatures up to 180 °C




► Plunger material stainless steel




Design N01
Cable entry M12 x 1.5



Dimension drawings



Design N01
Cable entry M12 x 1.5



Wiring diagrams



Technical data

Housing material	Die-cast aluminum, anodized			Die-cast aluminum, anodized		
Degree of protection according to IEC 60529	IP 67			IP 67		
Ambient temperature [°C]	-5...+80			-5...+180		
Plunger type	Chisel	Roller	Ball	Chisel	Roller	Ball
Operating point accuracy ¹⁾ [mm]	± 0.02	± 0.05	± 0.03	± 0.02	± 0.05	± 0.03
Approach speed max. ²⁾ [m/min]	20	50	8	20	50	8
Approach speed, min. [m/min]	0.01			0.01		
Actuating force, max. [N]	15			15		
Switching element	ES550		ES562	ES572		
Switching contact	1 changeover contact			1 changeover contact		
Switching principle	Snap-action switching contact			Snap-action switching contact		
Mechanical life	1 x 10 ⁷ operating cycles			1 x 10 ⁷ operating cycles		
Rated impulse withstand voltage U _{imp} [kV]	2.5			2.5		
Rated insulation voltage U _i [V]	250			250		
Utilization category acc. to IEC 60947-5-1	AC-15 U _e 230V I _e 2A DC-13 U _e 24V I _e 2A	DC-13 U _e 30V I _e 100mA		AC-15 U _e 230V I _e 4A DC-13 U _e 24V I _e 1A		
Contact material	Silver, gold-plated		Gold alloy	Fine silver		
Switching current, min. at [mA]	10		5	10		
Switching current [V DC]	24		5	24		
Short circuit protection (control circuit fuse) [A gG]	4		0.125	4		
Connection type	Soldered connection, 1.0 mm ² max.			Soldered connection, 1.0 mm ² max.		

1) The reproducible operating point accuracy relates to axial actuation, after run-in of approx. 2000 operating cycles.

2) The approach speed applies for a trip dog approach angle of 30°, 100 mm long, hardened and ground.

3) For mating connector see page 42 and 43.

Ordering table


Plunger type		ES550	ES562	ES572
Chisel plunger		084 902 N01D550-M	087 151 N01D562-M	087 162 N01D572-M
Roller plunger	R = 2.5 mm	084 903 N01R550-M	085 243 N01R562-M	087 163 N01R572-M
Ball plunger		084 904 N01K550-M	087 152 N01K562-M	087 164 N01K572-M

Position Switches




Design N01
Cable gland M12 x 1.5



Dimension drawings





Wiring diagrams



Design N01
Connection cable, length 5 m



Design N01
M12 plug adjustable, 4-pin + PE



Die-cast aluminum, anodized			Die-cast aluminum, anodized			Die-cast aluminum, anodized		
IP 67			IP 67			IP 67		
-5...+80			-5...+80			Mating connector inserted and screwed tight		
Chisel	Roller	Ball	Chisel	Roller	Ball	Chisel	Roller	Ball
± 0.02	± 0.05	± 0.03	± 0.02	± 0.05	± 0.03	± 0.02	± 0.05	± 0.03
20	50	8	20	50	8	20	50	8
0.01			0.01			0.01		
15			15			15		
ES550			ES550			ES550		ES562
1 changeover contact			1 changeover contact			1 changeover contact		
Snap-action switching contact			Snap-action switching contact			Snap-action switching contact		
1 x 10 ⁷ operating cycles			1 x 10 ⁷ operating cycles			1 x 10 ⁷ operating cycles		
2.5			2.5			2.5		
250			250			50	50	
AC-15 U _e 230V I _e 2A			AC-15 U _e 230V I _e 2A			AC-15 U _e 30V I _e 2A	DC-13 U _e 30V I _e 100mA	
DC-13 U _e 24V I _e 2A			DC-13 U _e 24V I _e 2A			DC-13 U _e 24V I _e 3A	Gold alloy	
Silver, gold-plated			Silver, gold-plated			Silver, gold-plated	Gold alloy	
10			10			10	5	
24			24			24	5	
4			4			4	0.125	
Soldered connection, 1.0 mm ² max.			PUR cable 4 x 0.5 mm ²			Plug connector M12 ³⁾		

ES550	ES550	ES550	ES562
085 708	088 978	088 623	-
N01D550-MC2018	N01D550X5000-M	N01D550SVM5-M	
094 856	088 982	088 622	093 426
N01R550-MC2018	N01R550X5000-M	N01R550SVM5-M	N01R562SVM5-M
089 619	088 986	088 624	-
N01K550-MC2018	N01K550X5000-M	N01K550SVM5-M	



Position Switches



Precision single limit switches

► Plunger material stainless steel

For plug connector with LED display



For operating voltage 230 V





Design N01
M12 plug, 4-pin

Design N01
M12 plug, 4-pin + PE





Dimension drawings



⚠ To achieve the positively driven travel, the dimension (I10.5) must be maintained by the trip dog. Actuating elements such as dog approach guides must be firmly mounted in accordance with EN 1088, i.e. riveted, welded or otherwise secured against becoming loose.

Wiring diagrams



Technical data

Housing material	Die-cast aluminum, anodized			Die-cast aluminum, anodized		
Degree of protection according to IEC 60529	IP 67			IP 67		
Ambient temperature [°C]	-5...+80			-5...+80		
Plunger type	Chisel	Roller	Ball	Chisel	Roller	Ball
Operating point accuracy ¹⁾ [mm]	± 0.02	± 0.05	± 0.03	± 0.02	± 0.05	± 0.03
Approach speed max. ²⁾ [m/min]	20	50	8	20	50	8
Approach speed, min. [m/min]	0.01			0.01		
Actuating force, max. [N]	15			15		
Switching element	ES550			ES550		
Switching contact	1 changeover contact			1 changeover contact		
Switching principle	Snap-action switching contact			Snap-action switching contact		
Mechanical life	1 x 10 ⁷ operating cycles			1 x 10 ⁷ operating cycles		
Rated impulse withstand voltage U _{imp} [kV]	2.5			2.5		
Rated insulation voltage U _i [V]	50			250		
Utilization category acc. to IEC 60947-5-1	DC-13 U _e 24V I _e 2A			AC-15 U _e 230V I _e 2A DC-13 U _e 24V I _e 2A		
Contact material	Silver, gold-plated			Silver, gold-plated		
Switching current, min. at [mA]	10			10		
Switching current [V DC]	24			24		
Short circuit protection (control circuit fuse) [A gG]	4			4		
Connection type	Plug connector M12 ³⁾			Plug connector M12, B-coded ³⁾		

1) The reproducible operating point accuracy relates to axial actuation, after run-in of approx. 2000 operating cycles.

2) The approach speed applies for a trip dog approach angle of 30°, 100 mm long, hardened and ground.

3) For mating connector see page 42 and 43.

Ordering table

Plunger type	ES550	ES550
Chisel plunger	091 003 N01D550-MC1526	-
Roller plunger R = 2.5 mm	091 001 N01R550-MC1526	091 257 N01R550SEM5-M
Ball plunger	091 002 N01K550-MC1526	-

Position Switches



With safety switching element






Design NB01
Cable entry M12 x 1.5





Design NB01
Cable entry M12 x 1.5

Design SN01
Cable entry M16 x 1.5

Dimension drawings



Wiring diagrams



Die-cast aluminum, anodized		Die-cast aluminum, anodized			Die-cast aluminum, anodized		
IP 67		IP 67			IP 67		
-25...+60		-5...+80			-5...+80		
Chisel ± 0.02	Roller ± 0.05	Chisel ± 0.02	Roller ± 0.05	Ball ± 0.03	Chisel ± 0.02	Roller ± 0.05	Ball ± 0.03
20	50	20	50	8	20	50	8
0.01		0.01			0.01		
15		15			15		
ES588		ES556			ES553	ES558	
1 NC contact		1 changeover contact			1 changeover contact	1 NO + 1 NC	
Snap-action switching contact		Snap-action switching contact			Snap-action switching contact		
1 x 10 ⁷ operating cycles		1 x 10 ⁷ operating cycles			1 x 10 ⁷ operating cycles		
2.5		2.5			2.5		
250		250			250		
AC-15 U _e 230V I _e 4A DC-13 U _e 24V I _e 3A		AC-15 U _e 230V I _e 2A DC-13 U _e 24V I _e 2A			AC-15 U _e 230V I _e 2A DC-13 U _e 24V I _e 2A	AC-15 U _e 230V I _e 4A DC-13 U _e 24V I _e 3A	
Fine silver		Silver, gold-plated			Silver, gold-plated	Silver	
1		-			-	10	
5		-			-	5	
10		4			4	4	
Screw terminal, 1.0 mm ² max.		Screw terminal, 1.0 mm ² max.			Screw terminal, 1.0 mm ² , max.	Soldered connection, 1.0 mm ² , max.	

ES588	ES556	ES553	ES558
088 584 NB01D588-M	085 245 NB01D556-M	085 252 SN01D553-M	085 260 SN01D558-M
088 583 NB01R588-M	085 246 NB01R556-M	085 253 SN01R553-M	085 261 SN01R558-M
-	085 247 NB01K556-M	085 254 SN01K553-M	085 262 SN01K558-M



Position Switches



Precision single limit switches





► Plunger material stainless steel

Design SN01
M12 plug adjustable, 4-pin + PE

Design SN01
Connection cable, length 2 m





Dimension drawings



⚠ To achieve the positively driven travel, the dimension (12.0.5) must be maintained by the trip dog. Actuating elements such as dog approach guides must be firmly mounted in accordance with EN 1088, i.e. riveted, welded or otherwise secured against becoming loose.

Wiring diagrams



Technical data

Housing material	Die-cast aluminum, anodized			Die-cast aluminum, anodized
Degree of protection according to IEC 60529	IP 67			IP 67
Ambient temperature [°C]	-5...+80			-5...+80
Plunger type	Chisel	Roller	Ball	Roller
Operating point accuracy ¹⁾ [mm]	± 0.02	± 0.05	± 0.03	± 0.05
Approach speed max. ²⁾ [m/min]	20	50	8	50
Approach speed, min. [m/min]	0.01			0.01
Actuating force, max. [N]	15			15
Switching element	ES558			ES558
Switching contact	1 NO contact + 1 NC contact			1 NO contact + 1 NC contact
Switching principle	Snap-action switching contact			Snap-action switching contact
Mechanical life	1 x 10 ⁷ operating cycles			1 x 10 ⁷ operating cycles
Rated impulse withstand voltage U _{imp} [kV]	2.5			2.5
Rated insulation voltage U _i [V]	30			250
Utilization category acc. to IEC 60947-5-1	AC-15 U _e 36V I _e 4A DC-13 U _e 24V I _e 3A			AC-15 U _e 230V I _e 4A DC-13 U _e 24V I _e 3A
Contact material	Silver			Silver
Switching current, min. at [mA]	10			10
Switching current [V DC]	5			5
Short circuit protection (control circuit fuse) [A gG]	4			4
Connection type	Plug connector M12 ⁵⁾			PUR cable 5 x 0.5 mm ²

1) The reproducible operating point accuracy relates to axial actuation, after run-in of approx. 2000 operating cycles.

2) The approach speed applies for a trip dog approach angle of 30°, 100 mm long, hardened and ground.

3) Version with bearing for high speeds and long travel distances on request.

Ordering table

Plunger type	ES558	ES558
Chisel plunger	088 625 SN01D558SVM5-M	-
Roller plunger SN01: R = 2.5 mm N1A: R = 4.0 mm	088 626 SN01R558SVM5-M	090 515 SN01R558X2000-M
Ball plunger	088 627 SN01K558SVM5-M	-
Dome plunger	-	-



Position Switches




With safety switching element




Design N1A
Cable entry M16 x 1.5



Dimension drawings



Wiring diagrams





Design N1A
Cable entry M16 x 1.5



With safety switching element



Design N1A
M12 plug adjustable, 4-pin + PE



Die-cast aluminum, anodized			Die-cast aluminum, anodized			Die-cast aluminum, anodized		
IP 67			IP 67			IP 67		
-25...+80			-5...+80			Mating connector inserted and screwed tight -25...+80		
Chisel	Roller	Dome	Chisel	Roller ³⁾	Ball	Chisel	Roller	Dome
± 0.002	± 0.01	± 0.002	± 0.002	± 0.01	± 0.01	± 0.002	± 0.01	± 0.002
40	80	10	40	80	10	40	80	10
0.01			0.01			0.01		
≥ 15	≥ 30		≥ 20			≥ 30		
ES508 ⁴⁾		ES514	ES502E ⁴⁾			ES514		
1 NC contact		1 NO + 1 NC	1 NO contact + 1 NC contact			1 NO contact + 1 NC contact		
Slow-action		Snap-action	Snap-action switching contact			Snap-action switching contact		
30 x 10 ⁶ op. cycles		1 x 10 ⁶ op. cycles	30 x 10 ⁶ operating cycles			1 x 10 ⁶ operating cycles		
2.5			2.5			2.5		
250			250			30		
AC-15 U _e 230V I _e 6A	AC-15 U _e 230V I _e 2.5A		AC-12 U _e 230V I _e 10A / AC-15 U _e 230V I _e 6A			AC-15 U _e 36V I _e 2.5A		
DC-13 U _e 24V I _e 6A	DC-13 U _e 24V I _e 6A		DC-13 U _e 24V I _e 6A			DC-13 U _e 24V I _e 4A		
Silver, gold-plated			Silver, gold-plated			Silver, gold-plated		
10	5		10			5		
24	24		24			24		
10			10			4		
Screw terminal 0.34 ... 1.5 mm ²			Screw terminal 0.34 ... 1.5 mm ²			Plug connector M12 ⁵⁾		

4) Version with LED function display AC/DC 10-60V or AC 110/230 V on request.

5) For mating connector see page 42 and 43.

ES508	ES514	ES502E	ES514
083 886 N1AD508-M	083 849 N1AD514-M	079 265 N1AD502-M	087 603 N1AD514SVM5-M
083 887 N1AR508-M	078 487 N1AR514-M	078 485 N1AR502-M	087 604 N1AR514SVM5-M
-	-	083 847 N1AK502-M	-
087 205 N1AW508-M	083 850 N1AW514-M	-	090 743 N1AW514SVM5-M



Position Switches



Precision single limit switches

► Plunger material stainless steel



For plug connectors with LED indicator




Design N1A
M12 plug adjustable, 4-pin + PE



Design N1A
M12 plug adjustable, 4-pin + PE




Dimension drawings



* Free position dimension applies for all plunger types





* Free position dimension applies for all plunger types



⚠ To achieve the positively driven travel, the dimension (31.0.5) must be maintained by the trip dog. Actuating elements such as dog approach guides must be firmly mounted in accordance with EN 1088, i.e. riveted, welded or otherwise secured against becoming loose.

Wiring diagrams



Technical data

Housing material		Die-cast aluminum, anodized			Die-cast aluminum, anodized		
Degree of protection according to IEC 60529		IP 67			IP 67		
Ambient temperature	[°C]	-5...+80			-5...+80		
Plunger type		Chisel	Roller	Ball	Chisel	Roller	Ball
Operating point accuracy ¹⁾	[mm]	± 0.002	± 0.01	± 0.01	± 0.002	± 0.01	± 0.01
Approach speed max. ²⁾	[m/min]	40	80	10	40	80	10
Approach speed, min.	[m/min]	0.01			0.01		
Actuating force, max.	[N]	≥ 20			≥ 20		
Switching element		ES502E			ES502E		
Switching contact		1 NO contact + 1 NC contact			1 NO contact + 1 NC contact		
Switching principle		Snap-action switching contact			Snap-action switching contact		
Mechanical life		30 x 10 ⁶ operating cycles			30 x 10 ⁶ operating cycles		
Rated impulse withstand voltage U _{imp}	[kV]	2.5			2.5		
Rated insulation voltage U _i	[V]	50			50		
Utilization category acc. to IEC 60947-5-1		AC-15 U _e 30V I _e 4A DC-13 U _e 24V I _e 4A			AC-15 U _e 30V I _e 4A DC-13 U _e 24V I _e 4A		
Contact material		Silver, gold-plated			Silver, gold-plated		
Switching current, min. at	[mA]	10			10		
Switching current	[V DC]	24			24		
Short circuit protection (control circuit fuse)	[A gG]	4			4		
Connection type		Plug connector M12 ⁴⁾			Plug connector M12 ⁴⁾		

1) The reproducible operating point accuracy relates to axial actuation, after run-in of approx. 2000 operating cycles.
2) The approach speed applies for a trip dog approach angle of 30°, 100 mm long, hardened and ground.

Ordering table

Plunger type		ES502E	ES502E
Chisel plunger		087 487 N1AD502SVM5-M	091 471 N1AD502SVM5-MC1883
Roller plunger	N1A: R = 4.0 mm N1A...AM: R = 2.5 mm	087 488 N1AR502SVM5-M	On request
Ball plunger		087 489 N1AK502SVM5-M	087 496 N1AK502SVM5-MC1883
Extended roller plunger		-	-



Position Switches




With safety switching element




Design N1A, extended roller plunger
Cable entry M16 x 1.5


Dimension drawings




Wiring diagrams



Design N1A, extended roller plunger
Cable entry M16 x 1.5




Wiring diagrams




With exterior diaphragm



Design N1A
Cable entry M16 x 1.5



Wiring diagrams



Die-cast aluminum, anodized		Die-cast aluminum, anodized		Die-cast aluminum, anodized		
IP 67		IP 67		IP 67		
-25...+80		-5...+80		-5...+80 (ES502E)		-25...+80 (ES508)
Extended roller		Extended roller		Chisel	Roller	Ball
0.1		0.1		± 0.002	± 0.01	± 0.01
20		20		40	80	10
0.01		0.01		0.01		
≥ 15	≥ 30	≥ 20		≥ 20	≥ 15	
ES508	ES514	ES502E ³⁾		ES502E	ES508	
1 NC contact	1 NO + 1 NC	1 NO contact + 1 NC contact		1 NO + 1 NC	1 NC contact	
Slow-action	Snap-action	Snap-action switching contact		Snap-action	Slow-action	
30 x 10 ⁶ op. cycles	1 x 10 ⁶ op. cycles	30 x 10 ⁶ operating cycles		30 x 10 ⁶ operating cycles		
2.5		2.5		2.5		
250		250		250		
AC-15 U _e 230V I _e 6A DC-13 U _e 24V I _e 6A	AC-15 U _e 230V I _e 2.5A DC-13 U _e 24V I _e 6A	AC-12 U _e 230V I _e 10A AC-15 U _e 230V I _e 6A DC-13 U _e 24V I _e 6A		AC-12 U _e 230V I _e 10A AC-15 U _e 230V I _e 6A DC-13 U _e 24V I _e 6A	AC-15 U _e 230V I _e 6A DC-13 U _e 24V I _e 6A	
Silver, gold-plated		Silver, gold-plated		Silver, gold-plated		
10	5	10		10		
24	24	24		24		
10		10		10		
Screw terminal 0.34 ... 1.5 mm ²		Screw terminal 0.34 ... 1.5 mm ²		Screw terminal 0.34 ... 1.5 mm ²		

3) Version with LED function display AC/DC 10-60V or AC 110/230 V on request.
4) For mating connector see page 42 and 43.

ES508	ES514	ES502E	ES502E	ES508
-	-	-	090 542 N1AD502AM-M	090 546 N1AD508AM-M
-	-	-	090 541 N1AR502AM-M	090 547 N1AR508AM-M
-	-	-	091 059 N1AK502AM-M	-
087 147 N1ARL508-M	087 204 N1ARL514-M	083 848 N1ARL502-M	-	-



Position Switches



Precision single limit switches



► Plunger material stainless steel





Design N10
Cable entry M20 x 1.5

Design N10, extended roller plunger
Cable entry M20 x 1.5

Dimension drawings



Wiring diagrams



Technical data

Housing material	Die-cast aluminum, anodized			Die-cast aluminum, anodized
Degree of protection according to IEC 60529	IP 67			IP 67
Ambient temperature [°C]	-5...+80			-5...+80
Plunger type	Chisel	Roller	Ball	Extended roller
Operating point accuracy ¹⁾ [mm]	± 0.002	± 0.01	± 0.01	± 0.1
Approach speed max. ²⁾ [m/min]	40	80	10	20
Approach speed, min. [m/min]	0.01			0.01
Actuating force, max. [N]	≥ 20			≥ 20
Switching element	ES502V			ES502V
Switching contact	1 NO contact + 1 NC contact			1 NO contact + 1 NC contact
Switching principle	Snap-action switching contact			Snap-action switching contact
Mechanical life	30 x 10 ⁶ operating cycles			30 x 10 ⁶ operating cycles
Rated impulse withstand voltage U _{imp} [kV]	2.5			2.5
Rated insulation voltage U _i [V]	250			250
Utilization category acc. to IEC 60947-5-1	AC-12 U _e 230V I _e 16A/AC-15 U _e 230V I _e 10A DC-13 U _e 24V I _e 6A			AC-12 U _e 230V I _e 16A/AC-15 U _e 230V I _e 10A DC-13 U _e 24V I _e 6A
Contact material	Silver, gold-plated			Silver, gold-plated
Switching current, min. at [mA]	20			20
Switching current [V DC]	24			24
Short circuit protection (control circuit fuse) [A gG]	16			16
Connection type	Screw terminal, 1.5 mm ² max.			Screw terminal, 1.5 mm ² max.

1) The reproducible operating point accuracy relates to axial actuation, after run-in of approx. 2000 operating cycles.

2) The approach speed applies for a trip dog approach angle of 30°, 100 mm long, hardened and ground.

Ordering table

Plunger type	ES502V	ES502V
Chisel plunger	086 293 N10D-M	-
Roller plunger	086 294 N10R-M	-
Ball plunger	088 589 N10K-M	-
Extended roller plunger	-	088 587 N10RL-M

Position Switches



EUCHNER





Design N11 Cable entry M20 x 1.5

Design N11, extended roller plunger Cable entry M20 x 1.5

Dimension drawings



Wiring diagrams



Die-cast aluminum, anodized			Die-cast aluminum, anodized		
IP 67			IP 67		
-5...+80			-5...+80		
Chisel	Roller	Ball	Extended roller		
± 0.002	± 0.01	± 0.01	± 0.1		
40	80	10	20		
0.01			0.01		
≥ 20			≥ 20		
ES502V			ES502V		
1 NO contact + 1 NC contact			1 NO contact + 1 NC contact		
Snap-action switching contact			Snap-action switching contact		
30 x 10 ⁶ operating cycles			30 x 10 ⁶ operating cycles		
2.5			2.5		
250			250		
AC-12 U _e 230V I _e 16A/AC-15 U _e 230V I _e 10A			AC-12 U _e 230V I _e 16A/AC-15 U _e 230V I _e 10A		
DC-13 U _e 24V I _e 6A			DC-13 U _e 24V I _e 6A		
Silver, gold-plated			Silver, gold-plated		
20			20		
24			24		
16			16		
Screw terminal, 1.5 mm ² max.			Screw terminal, 1.5 mm ² max.		

ES502V	ES502V
086 298 N11D-M	-
086 313 N11R-M	-
088 585 N11K-M	-
-	086 299 N11RL-M




Inductive Single Limit Switches

Inductive single limit switches are non-contact in operation. They are used as an alternative to mechanical switches. The main advantage is their wear-free operating mode. They are noted for their insensitivity to corrosive ambient conditions and their virtually unlimited mechanical life.

Features

- ▶ High actuating velocity and high operating frequency
- ▶ Resistant to strong vibrations and coarse soiling
- ▶ Resistant to most cutting oils and coolants
- ▶ Replacement for precision single limit switch of the same design



Position Switches




Inductive single limit switch design ENA, DC version

- ▶ Housing according to DIN 43693
- ▶ Rated operating distance 5 mm
- ▶ LED function display optional





Design ENA
Cable entry M16 x 1.5

Dimension drawings



Wiring diagrams



Technical data

Parameters	Value	Unit
Rated operating distance s_n	5	mm
Assured operating distance s_a	0...4	mm
Switching function	NO + NC	
Output	PNP or NPN (see Ordering table)	
LED function display	See ordering table	
Operating voltage U_B	DC 10...55	V
Voltage drop U_d	≤ 2.5	V
Rated insulation voltage U_i	DC 60	V
Rated operating current I_e	≤ 250	mA
Off-state current I_r	≤ 0.001	mA
No-load current I_0	≤ 15	mA
Short circuit and overload protection, pulsed	Yes	
Reverse polarity protection	Yes	
Wire break safety	Yes	
EMC compliance as per	IEC 60947-5-2	
Hysteresis H	≤ 0.5	mm
Repeat accuracy R	≤ 5	%
Switching frequency f	≤ 500	Hz
Utilization category according to IEC 60 947-5-2	DC-13	
Housing material	Die-cast aluminum, anodized	
Material for the sensing face	PBT	
Degree of protection according to IEC 60529	IP 67	
Ambient temperature T	- 25...+ 70	°C
Connection type	Screw terminal	
Conductor cross-section, max.	2 x 1.5 (per contact)	mm ²
Weight	0,2	kg

Ordering table

LED function display		PNP	NPN
With	Item	ENA10B050UP048LKK10-M	On request
	Order No.	ENA 086 280	
Without	Item	ENA10B050UP048NKK10-M	ENA10B050UN048NKK10-M
	Order No.	ENA 086 099	ENA 086 282

Position Switches

EUCHNER


Inductive single limit switch design ENA, AC version

- ▶ Housing according to DIN 43693
- ▶ Rated operating distance 5 mm




Design ENA
Cable entry M16 x 1.5


Dimension drawings



Wiring diagrams



AC NO



AC NC

Technical data

Parameters	Value	Unit
Rated operating distance s_n	5	mm
Assured operating distance s_a	0...4	mm
Switching function	NO or NC (see Ordering table)	
Output	AC	
LED function indicator on the switching element	Yes	
Short circuit protection	No	
Operating voltage U_B	AC 20...250	V
Voltage drop U_d	≤ 8	V
Rated insulation voltage U_i	AC 250	V
Rated operating current I_e	≤ 250	mA
Inrush current I_k (20 ms)	1.5	A
Off-state current I_r	$110\text{ V} \leq 1.5 / 230\text{ V} \leq 2.0$	mA
Minimum operating current I_m	5	mA
EMC compliance as per	IEC 60947-5-2	
Hysteresis H	≤ 0.5	mm
Repeat accuracy R	≤ 5	%
Switching frequency f	≤ 10	Hz
Utilization category according to IEC 60 947-5-2	AC-140	
Rated supply frequency	50 ... 60	Hz
Housing material	Die-cast aluminum, anodized	
Material for the sensing face	PBT	
Degree of protection according to IEC 60529	IP 67	
Ambient temperature T	- 25...+ 70	°C
Connection type	Screw terminal	
Max. conductor cross-section	2 x 1.5 (per contact)	mm ²
Weight	0.2	kg

Ordering table

LED function display	NO	NC
On the switching element	ENA10B050AW250NNK10-M	ENA10B050RW250NNK10-M
Item		
Order No.	ENA 086 284	ENA 088 775

LED visible from the exterior on request.



Position Switches




Inductive single limit switch design ESN, DC version

- ▶ Compact design with connection cable
- ▶ Rated operating distance 5 mm
- ▶ LED function display



Design ESN
Connection cable 5 m PUR



Dimension drawings



Wiring diagrams



Technical data

Parameters	Value	Unit
Rated operating distance s_n	5	mm
Assured operating distance s_a	0...4	mm
Output and switching function	PNP NO or NO + NC (see Ordering table)	
LED function display	Yes	
Operating voltage U_B	DC 10...55	V
Voltage drop U_d	≤ 2.5	V
Rated insulation voltage U_i	DC 60	V
Rated operating current I_e	≤ 250	mA
Off-state current I_r	≤ 0.05	mA
No-load current I_0	≤ 15	mA
Short circuit and overload protection, pulsed	Yes	
Reverse polarity protection	Yes	
Wire break safety	Yes	
EMC compliance as per	IEC 60947-5-2	
Hysteresis H	≤ 0.5	mm
Repeat accuracy R	≤ 5	%
Switching frequency f	≤ 500	Hz
Utilization category according to IEC 60 947-5-2	DC-13	
Housing material	Die-cast aluminum, anodized	
Material for the sensing face	PBT	
Degree of protection according to IEC 60529	IP 67	
Ambient temperature T	- 25...+ 70	°C
Connection	NO NO + NC	PUR cable 3 x 0.25 PUR cable 4 x 0.25
Weight	0.3	mm ² kg

Ordering table

Connection cable		PNP NO	PNP NO + NC
5 m PUR	Item	ESN10B050AP048LK05P-M	ESN10B050UP048LK05P-M
	Order No.	ESN 088 769	ESN 088 771

Other cable lengths on request. Output NPN NO + NC on request.

Position Switches




Inductive single limit switch design ESN, DC version

- ▶ Compact design with plug connector
- ▶ Rated operating distance 5 mm
- ▶ LED function display




Design ESN
Plug connector M12, 4-pin

Dimension drawings




For plug connector see page 42/43

Wiring diagrams



DC NO, PNP



DC NO + NC, PNP

Technical data

Parameters	Value	Unit
Rated operating distance s_n	5	mm
Assured operating distance s_a	0...4	mm
Output and switching function	PNP NO or PNP NO + NC (see Ordering table)	
LED function display	Yes	
Operating voltage U_B	DC 10...55	V
Voltage drop U_d	≤ 2.5	V
Rated insulation voltage U_i	DC 60	V
Rated operating current I_e	≤ 250	mA
Off-state current I_r	≤ 0.05	mA
No-load current I_0	≤ 15	mA
Short circuit and overload protection, pulsed	Yes	
Reverse polarity protection	Yes	
Wire break safety	Yes	
EMC compliance as per	IEC 60947-5-2	
Hysteresis H	≤ 0.5	mm
Repeat accuracy R	≤ 5	%
Switching frequency f	≤ 500	Hz
Utilization category according to IEC 60 947-5-2	DC-13	
Housing material	Die-cast aluminum, anodized	
Material for the sensing face	PBT	
Degree of protection according to IEC 60529	IP 67	
Ambient temperature T	- 25...+ 70	°C
Connection	Plug connector M12 ¹⁾	
Weight	0.1	kg

1) Degree of protection only guaranteed on the usage of the plug connector on page 42 and 43.

Ordering table

Plug connector system		PNP NO	PNP NO + NC
Plug connector S01	Item	ESN10B050AP048LKS01-M	ESN10B050UP048LKS01-M
(M12, 4-pin)	Order No.	ESN 090 439	ESN 088 770



Position Switches




Inductive single limit switch design ESN, AC version

- ▶ Compact design with connection cable
- ▶ Rated operating distance 5 mm
- ▶ LED function display





Design ESN
Connection cable 5 m PVC

Dimension drawings



Wiring diagrams



Technical data

Parameters	Value	Unit
Rated operating distance s_n	5	mm
Assured operating distance s_a	0...4	mm
Switching function	NO or NC (see Ordering table)	
Output push-pull +U	AC	
LED function display	Yes	
Short circuit protection	No	
Operating voltage U_B	AC 20...250	V
Voltage drop U_d	≤ 8	V
Rated insulation voltage U_i	AC 250	V
Rated operating current I_e	≤ 250	mA
Inrush current I_k (20 ms)	1.5	A
Off-state current I_r	$110 V \leq 1.5 / 230 V \leq 2.0$	mA
Minimum operating current I_m	5	mA
EMC compliance as per	IEC 60947-5-2	
Hysteresis H	≤ 0.5	mm
Repeat accuracy R	≤ 5	%
Switching frequency f	≤ 10	Hz
Utilization category according to IEC 60 947-5-2	AC-140	
Rated supply frequency	50 ... 60	Hz
Housing material	Die-cast aluminum, anodized	
Material for the sensing face	PBT	
Degree of protection according to IEC 60529	IP 67	
Ambient temperature T	- 25...+ 70	°C
Connection type	PVC cable 3 x 0.5	mm ²
Weight	0.3	kg

Ordering table

Connection cable		NO	NC
5 m PVC	Item	ESN10B050AW250LN05V-M	ESN10B050RW250LN05V-M
	Order No.	ESN 088 773	ESN 088 774

Other cable lengths on request.

Position Switches

EUCHNER

Round connectors

- ▶ Straight design and elbow connector
- ▶ Screw connection
- ▶ Sprayed cable
- ▶ 4 and 5-pin




Straight plug connector M12

4-pin / 4-pin + PE


Straight plug connector M12, coded

4-pin + PE


Dimension drawings




Dimension drawings



Wiring diagrams



Wiring diagrams



Technical data

Number of pins	4	4+PE	4+PE
Housing material	TPU self-extinguishing		TPU self-extinguishing
Grip	TPU self-extinguishing		TPU self-extinguishing
Contact carrier	TPU self-extinguishing		TPU self-extinguishing
Sheath material	PUR, halogen-free, flame retardant		PVC, halogen-free, flame retardant
Sheath color	Black		Orange
Degree of protection according to IEC 60529 (inserted and screwed tight)	IP 67		IP 67
Ambient temperature [°C]	-25 ... +80		-25 ... +90
Contact material	CuSn nickel-plated, 0.3 µm gold-plated		CuSn nickel-plated, 0.8 µm gold-plated
Conductor cross-section [mm²]	4 x 0.34	5 x 0.5	4 x 0.34 / 1 x 0.5
Cable diameter [mm]	6		5
Contact resistance [mΩ]	≤ 5		≤ 5
Test voltage (60 s) [kV eff]	2	1.5	2
Rated voltage [V]	AC 250/DC 300	AC 30/DC 36	AC 250/DC 300
Rated current [A]	4		4

Ordering table

Plug connector M12, without LED, Connection cable 5 m	035 613 SGLF4-5000P	073 461 SGLF5-5000P	045 524 SGLF5PE-5000
Plug connector M12, with 3 LEDs, Connection cable 5 m	-	-	-

Position Switches







EUCHNER



Right-angle plug connector M12
4-pin / 4-pin + PE

Right-angle plug connector M12, coded
4-pin + PE

Plug connector M12 with 3 LEDs
4-pin



4		4+PE	4+PE	4
TPU self-extinguishing		TPU self-extinguishing	TPU self-extinguishing	TPU self-extinguishing
TPU self-extinguishing		TPU self-extinguishing	TPU self-extinguishing	TPU self-extinguishing
PUR, halogen-free, flame retardant		PVC, halogen-free, flame retardant	PVC, halogen-free, flame retardant	PUR, halogen-free, flame retardant
Black		Orange	Orange	Black
IP 67		IP 67	IP 67	IP 67
-25 ... +80		-25 ... +90	-25 ... +90	-25 ... +80
CuSn nickel-plated, 0.3 µm gold-plated		CuSn nickel-plated, 0.8 µm gold-plated	CuSn nickel-plated, 0.8 µm gold-plated	CuSn nickel-plated, 0.3 µm gold-plated
4 x 0.34	5 x 0.5	5 x 0.5	5 x 0.5	4 x 0.34
6	5	5	5	5
≤ 5	≤ 5	≤ 5	≤ 5	≤ 5
2	1.5	2	2	-
AC 250/DC 300	AC 30/DC 36	AC 250/DC 300	AC 250/DC 300	DC 10 ... 30
4	4	4	4	4

035 618 SWLF4-5000P	073 462 SWLF5-5000P	045 523 SWLF5PE-5000	-
-	-	-	041 091 SWLF4P-5000P



Position Switches



LED function display


On request, versions with voltage ranges AC 110/230 V are available.



Operating voltage [V]	Color	Item	Order No.
AC/DC 12 - 60	Red	LE 060 rt	035 495
	Green	LE 060 gr	035 496
	Yellow	LE 060 ge	035 497

Cable glands

Material nickel-plated brass, degree of protection IP 67



Item	Metric thread M	Cable outer diameter [mm]	A [mm]	B [mm]	E [mm]	SW [mm]	Order no.
EKVM12/04	M12 x 1.5	4 - 6.5	20	5	15.5	14	086 327
EKVM16/04	M16 x 1.5	4 - 6.5	20	6	20	18	086 328
EKVM16/06	M16 x 1.5	6.5 - 9.5	20	6	20	18	086 330
EKVM20/06	M20 x 1.5	6.5 - 9.5	20	6	24.4	22	077 683

Additional products

Trip rails/trip dogs

U-trip rails

enable the trip dogs to be adjusted from the switch side. The trips dogs can be installed and adjusted quickly and easily in any location.

U-trip dogs

are designed for usage in U-trip rails. They have an expansion plate clamp and enable precise adjustment, even when the limit switch is activated.

G-trip rails

enable the trip dogs to be adjusted from the side opposite the switch. They are made of steel and are protected from corrosion by a special surface treatment. Trip rails can be ordered pre-assembled or as a component for self-assembly.

G-trip dogs

are designed for use in G-trip rails. The trip dogs are clamped in the trip rail by a hexagon socket head screw with spring washer. This washer locks the trip dog in place even when the trip rail is in a vertical position and allows precise adjustment.

For detailed information see catalog for multiple limit switches.



Appendix

Terms and explanations


Rated operating distance s_n

The rated operating distance is a general variable used for measurement of operating distances. It does not take into account either the production tolerances or changes caused by external effects such as voltage and temperature.

Assured operating distance s_a


The assured operating distance is the operating distance at which correct operation of the inductive switching element is guaranteed within the permissible operating conditions (temperature and voltage).

The actuation distance lies between 0 and 81 % of the rated operating distance s_n .



Hysteresis H

The hysteresis is the difference in distance terms between the ON point as the test plate approaches and the OFF point as it moves away from the active face of the inductive switching element.



Repeat accuracy R

The repeat accuracy is the accuracy of the real operating distance s_r for two switching actions in succession within 8 hours at an operating temperature of $23 \pm 5^\circ\text{C}$ and an operating voltage of $U_B \pm 5\%$.

Operating voltage U_b

The operating voltage defines the voltage range in which the inductive switching element functions reliably. The specified values represent limits without any tolerances. The values can be obtained by referring to the technical data for the switching element. In the case of two-wire switching elements, this is applicable only in series connection with the load.

Voltage drop U_d

The voltage drop is measured across the active output of the inductive switching element when the output is in the "active energized" condition and when the rated operating current I_e flows.

Rated operating current I_e

The rated operating current is the nominal current which can load the inductive switching element in continuous operation.

Off-state current I_o

The off-state current is the current which flows in the load circuit of an inductive switching element in the non-conducting condition. In practical terms, this current has to be taken into account only for two-wire switching elements.

Minimum operating current I_m

The minimum operating current is the minimum current required for the function of a 2-wire switching element in active energized condition.

Inrush current I_k

The inrush current is the maximum current which can flow in an AC-2-wire switching element for a particular period at the moment it is switched on. The details in the technical data are valid for 20 ms.

Switching frequency f

The switching frequency is the maximum possible number of switching operations per second. This is determined according to IEC 60947-5-2 and is based on a mark-space ratio of 1:2. The switching frequency is a switch-specific variable and can be obtained by referring to the technical data for the switching element.

Ambient temperature T

The ambient temperature is the temperature range in which the reliable operation of the inductive switching element is guaranteed. This range is between -25 and $+70^\circ\text{C}$.

Temperature drift Δs

The temperature drift defines the offset in the switching point in $\mu\text{m}/\text{K}$ on a change in the ambient temperature from -25 to $+70^\circ\text{C}$ under otherwise constant measurement conditions.

Suppressor circuits

The inductive switching elements are largely protected against external interference by use of various circuit techniques (suppressor circuits).

For utilization category DC-13 the output is to be protected with a free-wheeling diode for inductive loads.

Short-circuit and overload protection

The inductive switching elements are designed so that short circuits cannot damage the outputs. **Pulsed short circuit protection** is used.

This means that the output transistor is switched off and on again in quick succession in the event of overloading or a short-circuit. In this way, it is possible to establish whether the fault is still present or has been rectified.

Transient protection

EUCHNER proximity switches are protected against interference caused by the occurrence of inductive voltage peaks in accordance with IEC 801-4.

The respective values are specified in the technical data. Testing is performed in accordance with the stipulations in DIN VDE 0660, Part 208 and IEC 947-5-2.

Wire break safety

The EUCHNER proximity switches with wire break safety are designed such that on a wire break on any connection, the switch does not output a spurious signal.

Reverse polarity protection

Protection against reverse polarization of the operating voltage.

Customized versions

Inductive switching elements according to NAMUR

These switching elements fulfill the specification IEC 60 947-5-6 and IEC 61 934.

The current consumption at $U_b = 8.2 \text{ V}$ is greater than 2.5 mA when the oscillator face is not activated and less than 1.0 mA when the oscillator face is activated. The current consumption characteristic is linear during the transition from the inactivated to the activated state of the oscillator face, i.e. these switches do not have a snap action.

DC-2-wire switching elements

Two-wire switching elements can be used in principle instead of mechanical switches. Their low off-state current makes them especially suitable for use in conjunction with programmable logic controllers.

Compared with three-wire switching elements they have the advantage of requiring less wiring.

Increased operating distance

For designs with 12 mm proximity switch spacing, switching elements with increased operating distance are available on request ($s_n = 5 \text{ mm}$).

Due to their technical characteristics, these switching elements can be used both with a pulsed operating voltage and an operating voltage that is not pulsed.

Item Index

EUCHNER

Index by item designation

Item	Order No.	Page	Item	Order No.	Page
EGM12-1200C1791	075 556	14	N01K550-MC1526	091 002	26
EGM12-1200C1820	076 464	14	N01K550-MC2018	089 619	25
EGM12-4000C1791	076 154	14	N01K550SVM5-M	088 624	25
EGM12SAM3C1868	077 228	15	N01K550X5000-M	088 986	25
EGM12SEM4	082 205	14	N01K562-M	087 152	24
EGM12SEM4C1820	093 733	14	N01K572-M	087 164	24
EGT1/4A2000	001 366	12	N01R550-M	084 903	24
EGT1/4A2000C2079	094 982	13	N01R550-MC1526	091 001	26
EGT1/4A2000C2137	102 476	13	N01R550-MC2018	094 856	25
EGT1/4A5000	001 368	12	N01R550SEM5-M	091 257	26
EGT1/4ASEM4	033 976	12	N01R550SVM5-M	088 622	25
EGT1/4ASEM4C1802	075 644	12	N01R550X5000-M	088 982	25
EGT1/4ASEM4C2088	095 278	13	N01R562-M	085 243	24
EGT1/4ASEM4C2137	098 071	13	N01R562SVM5-M	093 426	25
EGT1/4R2000	001 371	12	N01R572-M	087 163	24
EGT1/4R5000	001 372	12	N10D-M	086 293	32
EGT1/4RSEM4	033 982	12	N10K-M	088 589	32
EGT1/4RSEM4C2088	104 316	13	N10RL-M	088 587	32
EGT1/4RSEM4C2137	104 372	13	N10RM	086 294	32
EGT11A2NSFM5	093 352	11	N11D-M	086 298	33
EGT11R2NSFM5	091 848	11	N11K-M	088 585	33
EGT1-2000	001 732	16	N11RL-M	086 299	33
EGT12A5000	082 201	10	N11RM	086 313	33
EGT12ARSEM4C1888	078 483	11	N1AD502AM-M	090 542	31
EGT12ASFM5	075 426	10	N1AD502-M	079 265	29
EGT12ASFM5C2083	095 112	11	N1AD502SVM5-M	087 487	30
EGT12R5000	078 848	10	N1AD502SVM5-MC1883	091 471	30
EGT12RRSEM4C1888	079 139	11	N1AD508AM-M	090 546	31
EGT12RSFM5	075 427	10	N1AD508-M	083 886	29
EGT1-5000	001 733	16	N1AD514-M	083 849	29
EGT1M12-2000	092 695	15	N1AD514SVM5-M	087 603	29
EGT1M12-5000	093 364	15	N1AK502AM-M	091 059	31
EGT1M12SEM4	093 365	15	N1AK502-M	083 847	29
EGT1SEM4	019 727	16	N1AK502SVM5-M	087 489	30
EGT1SEM4C1613	054 250	17	N1AK502SVM5-MC1883	087 496	30
EGT1SEM4C1832	077 347	17	N1AR502AM-M	090 541	31
EGT2-2000	001 864	18	N1AR502-M	078 485	29
EGT2-5000	001 865	18	N1AR502SVM5-M	087 488	30
EGT2SEM4	052 504	18	N1AR508AM-M	090 547	31
EGT2SEM5	042 819	19	N1AR508-M	083 887	29
EGT3-2000	001 896	19	N1AR514-M	078 487	29
EGT3-5000	001 897	19	N1AR514SVM5-M	087 604	29
EGT3SEM4	070 834	19	N1ARL502-M	083 848	31
EGT4-10000	093 967	20	N1ARL508-M	087 147	31
EGT4-2000	094 339	20	N1ARL514-M	087 204	31
EGT4-5000	092 026	20	N1AW508-M	087 205	29
EGZ12-12-5000	094 823	21	N1AW514-M	083 850	29
EKVM12/04	086 327	44	N1AW514SVM5-M	090 743	29
EKVM16/04	086 328	44	NB01D556-M	085 245	27
EKVM16/06	086 330	44	NB01D588-M	088 584	27
EKVM20/06	077 683	44	NB01K556-M	085 247	27
ENA10B050AW250NNK10-M	ENA 086 284	37	NB01R556-M	085 246	27
ENA10B050RW250NNK10-M	ENA 088 775	37	NB01R588-M	088 583	27
ENA10B050UNO48NKK10-M	ENA 086 282	36	RGB02N12	084 511	22
ENA10B050UPO48LKK10-M	ENA 086 280	36	RGB04N12	084 514	22
ENA10B050UPO48NKK10-M	ENA 086 099	36	RGB06N12	084 510	22
ESN10B050APO48LK05P-M	ESN 088 769	38	SGLF4-5000P	035 613	42
ESN10B050APO48LKS01-M	ESN 090 439	39	SGLF5-5000P	073 461	42
ESN10B050AW250LN05V-M	ESN 088 773	40	SGLF5PE-5000	045 524	42
ESN10B050RW250LN05V-M	ESN 088 774	40	SN01D553-M	085 252	27
ESN10B050UPO48LK05P-M	ESN 088 771	38	SN01D558-M	085 260	27
ESN10B050UPO48LKS01-M	ESN 088 770	39	SN01D558SVM5-M	088 625	28
LE 060 ge	035 497	44	SN01K553-M	085 254	27
LE 060 gr	035 496	44	SN01K558-M	085 262	27
LE 060 rt	035 495	44	SN01K558SVM5-M	088 627	28
N01D550-M	084 902	24	SN01R553-M	085 253	27
N01D550-MC1526	091 003	26	SN01R558-M	085 261	27
N01D550-MC2018	085 708	25	SN01R558SVM5-M	088 626	28
N01D550SVM5-M	088 623	25	SN01R558X2000-M	090 515	28
N01D550X5000-M	088 978	25	SWLF4-5000P	035 618	43
N01D562-M	087 151	24	SWLF4P-5000P	041 091	43
N01D572-M	087 162	24	SWLF5-5000P	073 462	43
N01K550-M	084 904	24	SWLF5PE-5000	045 523	43

Item Index

EUCHNER

Index by order number

Order No.	Item	Page
001 366	EGT1/4A2000	12
001 368	EGT1/4A5000	12
001 371	EGT1/4R2000	12
001 372	EGT1/4R5000	12
001 732	EGT1-2000	16
001 733	EGT1-5000	16
001 864	EGT2-2000	18
001 865	EGT2-5000	18
001 896	EGT3-2000	19
001 897	EGT3-5000	19
019 727	EGT1SEM4	16
033 976	EGT1/4ASEM4	12
033 982	EGT1/4RSEM4	12
035 495	LE 060 rt	44
035 496	LE 060 gr	44
035 497	LE 060 ge	44
035 613	SGLF4-5000P	42
035 618	SWLF4-5000P	43
041 091	SWLF4P-5000P	43
042 819	EGT2SEM5	19
045 523	SWLF5PE-5000	43
045 524	SGLF5PE-5000	42
052 504	EGT2SEM4	18
054 250	EGT1SEM4C1613	17
070 834	EGT3SEM4	19
073 461	SGLF5-5000P	42
073 462	SWLF5-5000P	43
075 426	EGT12ASFM5	10
075 427	EGT12RSFM5	10
075 556	EGM12-1200C1791	14
075 644	EGT1/4ASEM4C1802	12
076 154	EGM12-4000C1791	14
076 464	EGM12-1200C1820	14
077 228	EGM12SAM3C1868	15
077 347	EGT1SEM4C1832	17
077 683	EKVM20/06	44
078 483	EGT12ARSEM4C1888	11
078 485	N1AR502-M	29
078 487	N1AR514-M	29
078 848	EGT12R5000	10
079 139	EGT12RRSEM4C1888	11
079 265	N1AD502-M	29
082 201	EGT12A5000	10
082 205	EGM12SEM4	14
083 847	N1AK502-M	29
083 848	N1ARL502-M	31
083 849	N1AD514-M	29
083 850	N1AW514-M	29
083 886	N1AD508-M	29
083 887	N1AR508-M	29
084 510	RGKB06N12	22
084 511	RGKB02N12	22
084 514	RGKB04N12	22
084 902	N01D550-M	24
084 903	N01R550-M	24
084 904	N01K550-M	24
085 243	N01R562-M	24
085 245	NB01D556-M	27
085 246	NB01R556-M	27
085 247	NB01K556-M	27
085 252	SN01D553-M	27
085 253	SN01R553-M	27
085 254	SN01K553-M	27
085 260	SN01D558-M	27
085 261	SN01R558-M	27
085 262	SN01K558-M	27
085 708	N01D550-MC2018	25
086 293	N10D-M	32
086 294	N10R-M	32
086 298	N11D-M	33
086 299	N11RL-M	33
086 313	N11R-M	33
086 327	EKVM12/04	44

Order No.	Item	Page
086 328	EKVM16/04	44
086 330	EKVM16/06	44
087 147	N1ARL508-M	31
087 151	N01D562-M	24
087 152	N01K562-M	24
087 162	N01D572-M	24
087 163	N01R572-M	24
087 164	N01K572-M	24
087 204	N1ARL514-M	31
087 205	N1AW508-M	29
087 487	N1AD502SVM5-M	30
087 488	N1AR502SVM5-M	30
087 489	N1AK502SVM5-M	30
087 496	N1AK502SVM5-MC1883	30
087 603	N1AD514SVM5-M	29
087 604	N1AR514SVM5-M	29
088 583	NB01R588-M	27
088 584	NB01D588-M	27
088 585	N11K-M	33
088 587	N10RL-M	32
088 589	N10K-M	32
088 622	N01R550SVM5-M	25
088 623	N01D550SVM5-M	25
088 624	N01K550SVM5-M	25
088 625	SN01D558SVM5-M	28
088 626	SN01R558SVM5-M	28
088 627	SN01K558SVM5-M	28
088 978	N01D550X5000-M	25
088 982	N01R550X5000-M	25
088 986	N01K550X5000-M	25
089 619	N01K550-MC2018	25
090 515	SN01R558X2000-M	28
090 541	N1AR502AM-M	31
090 542	N1AD502AM-M	31
090 546	N1AD508AM-M	31
090 547	N1AR508AM-M	31
090 743	N1AW514SVM5-M	29
091 001	N01R550-MC1526	26
091 002	N01K550-MC1526	26
091 003	N01D550-MC1526	26
091 059	N1AK502AM-M	31
091 257	N01R550SEM5-M	26
091 471	N1AD502SVM5-MC1883	30
091 848	EGT11R2NSFM5	11
092 695	EGT1M12-2000	15
092 026	EGT4-5000	20
093 352	EGT11A2NSFM5	11
093 364	EGT1M12-5000	15
093 365	EGT1M12SEM4	15
093 426	N01R562SVM5-M	25
093 733	EGM12SEM4C1820	14
093 967	EGT4-10000	20
094 339	EGT4-2000	20
094 823	EGZ12-12-5000	21
094 856	N01R550-MC2018	25
094 982	EGT1/4A2000C2079	13
095 112	EGT12ASFM5C2083	11
095 278	EGT1/4ASEM4C2088	13
098 071	EGT1/4ASEM4C2137	13
102 476	EGT1/4A2000C2137	13
104 316	EGT1/4RSEM4C2088	13
104 372	EGT1/4RSEM4C2137	13
ENA 086 099	ENA10B050UP048NKK10-M	36
ENA 086 280	ENA10B050UP048LKK10-M	36
ENA 086 282	ENA10B050UN048NKK10-M	36
ENA 086 284	ENA10B050AW250NNK10-M	37
ENA 088 775	ENA10B050RW250NNK10-M	37
ESN 088 769	ESN10B050AP048LK05P-M	38
ESN 088 770	ESN10B050UP048LKS01-M	39
ESN 088 771	ESN10B050UP048LK05P-M	38
ESN 088 773	ESN10B050AW250LN05V-M	40
ESN 088 774	ESN10B050RW250LN05V-M	40
ESN 090 439	ESN10B050AP048LKS01-M	39

Product Guide

Automation



Position Switches

- ▶ Position Switches
- ▶ Position Switches according to EN 50 041

Precision Multiple Limit Switches

Inductive Limit Switches

Plug Connectors

Trip Rails/Trip Dogs

Inductive Ident Systems

Safety



Safety Switches, Metal Housing

- ▶ Safety Switches NZ/TZ
- ▶ Safety Switches NX/TX

Safety Switches, Plastic Housing

- ▶ Safety Switches NM
- ▶ Safety Switches NP/GP/TP
- ▶ Safety Switches STM
- ▶ Safety Switches STP

Non-Contact Safety Switches

- ▶ Non-Contact Safety Switches CES/CEM,
Transponder Coding
- ▶ Non-Contact Safety Switches CMS,
Magnetic Coding

Safety Products with integrated Bus Interface

Bolts for Safety Guards

Enabling Switches

Safety Relays

- ▶ Safety Relays ESM
- ▶ Modular Safety System ESM-F

Rope Pull Switches

ManMachine



Joystick Switches

Electronic Handwheels

Pendant Stations

- ▶ Pendant Stations HBA
- ▶ Pendant Stations HBE/HBL

Electronic-Key-System

Representation international

Australia

Micromax Pty. Ltd.
PO Box 1238
Wollongong NSW 2500
Tel. +61-2-4271-1300
Fax +61-2-4271-8091
micromax@micromax.com.au

Austria

EUCHNER Ges.mBH
Süddruckgasse 4
2512 Tribuswinkel
Tel. +43-2252-421-91
Fax +43-2252-452-25
info@euchner.at

Benelux

EUCHNER (BENELUX) BV
Visschersbuurt 23
3350 AC Papendrecht
Tel. +31-78-6154-766
Fax +31-78-6154-311
info@euchner.nl

Brazil

EUCHNER Ltda
Av. Prof. Luiz Ignácio Anhaia Mello,
no. 4387
S. Lucas
São Paulo - SP - Brasil
CEP 03295-000
Tel. +55-11-2918-2200
Fax +55-11-2301-0613
euchner@euchner.com.br

Canada

IAC & Associates Inc.
1925 Provincial Road
Windsor, Ontario
N8W 5V7
Tel. +1-519-966-3444
Fax +1-519-966-6160
sales@iacnassociates.com

China

EUCHNER (Shanghai) Trading Co., Ltd.
Unit C, Floor 20
Cross Region Plaza
No. 899 Lingling Road
Xuhui District
Shanghai, 200030
Tel. +86-21-5774-7090
Fax +86-21-5774-7599
info@euchner.com.cn

Czech Republic

EUCHNER electric s.r.o.
Spielberk Office Center
Holandská
639 00 Brno
Tel. +420-533-443-150
Fax +420-533-443-153
info@euchner.cz

Denmark

Duelco A/S
Mommærkvej 5
6400 Sønderborg
Tel. +45-7010-1007
Fax +45-7010-1008
info@duelco.dk

Finland

Sähkölehto Oy
Holkkitie 14
00880 Helsinki
Tel. +358-9-774-6420
Fax +358-9-759-1071
office@sahkolehto.fi

France

EUCHNER France S.A.R.L.
Parc d'Affaires des Bellevues
Allée Rosa Luxembourg
Bâtiment le Colorado
95610 ERAGNY sur OISE
Tel. +33-1-3909-9090
Fax +33-1-3909-9099
info@euchner.fr

Hong Kong

Imperial Engineers & Equipment Co. Ltd.
Unit B 12/F Cheung Lee Industrial Building
9 Cheung Lee Street Chai Wan
Hong Kong
Tel. +852-2889-0292
Fax +852-2889-1814
info@imperial-elec.com

Hungary

EUCHNER Ges.mBH
Magyarországi Fióktelep
2045 Törökbálint
Tópark utca 1/a.
Tel. +36-2342-8374
Fax +36-2342-8375
info@euchner.hu

India

EUCHNER electric (India)
West End River View
40, First Floor
Survey No. 169/1
Aundh
Pune 411021
Tel. +91-20-6401 6384
Fax +91-20-2588 5148
euchner.in@gmail.com

TEKNIC CONTROLGEAR PVT. LTD.

703, Madhava,
Bandra Kurlia Complex
Bandra (East)
Mumbai 400051
Tel. +91-22-2659-2392
Fax +91-22-2659-2391
teknico@vsnl.com

Iran

INFOCELL IRAN CO.
84, Manoucheri Ave.
P.O. Box 81655-861
Isfahan
Tel. +98-311-2211-358
Fax +98-311-222-6176
info@infocell-co.com

Israel

Ilan At Gavish Automation Service Ltd.
26 Shenkar St. Qiryat Arie 49513
P.O. Box 10118
Petach Tikva 49001
Tel. +972-3-922-1824
Fax +972-3-924-0761
mail@ilan-gavish.com

Italy

TRITECNICA S.r.l.
Viale Lazio 26
20135 Milano
Tel. +39-02-5419-41
Fax +39-02-5501-0474
info@tritecnica.it

Japan

Solton Co. Ltd.
2-13-7, Shin-Yokohama
Kohoku-ku, Yokohama
Japan 222-0033
Tel. +81-45-471-7711
Fax +81-45-471-7717
sales@solton.co.jp

Korea

EUCHNER Korea Co., Ltd.
RM 810 Daerung Technotown 3rd
#448 Gasang-Dong
Kumchon-Gu, Seoul
Tel. +82-(02)-2107-3500
Fax +82-(02)-2107-3999
sijang@euchner.co.kr

Mexico

SEPIA S.A. de C.V.
Maricopa # 10
302, Col. Napoles.
Del. Benito Juarez
03810 Mexico D.F.
Tel. +52-55-5536-7787
Fax +52-55-5682-2347
sepia@prodigy.net.mx

New Zealand

W Arthur Fisher Limited
11 Te Apunga Place
Mt Wellington
Auckland
Tel. +64-9270-0100
Fax +64-9270-0900
christl@waf.co.nz

Norway

ELIS ELEKTRO AS
Jerikoveien 16
1067 Oslo
Tel. +47-22-9056-70
Fax +47-22-9056-71
post@eliselektro.no

Poland

ELTRON
Pl. Wolności 7B
50-071 Wrocław
Tel. +48-71-3439-755
Fax +48-71-3460-225
eltron@eltron.pl

Portugal

PAM Serviços Tecnicos Industriais Lda.
Rua de Timor - Pavilhão 2A
Zona Industrial da Abelheira
4785-123 TROFA
Tel. +351-252-418431
Fax +351-252-494739
pam@mail.telepac.pt

Republic of South Africa

RUBICON ELECTRICAL DISTRIBUTORS
4 Reith Street, Sidwell
6061 Port Elizabeth
Tel. +27-41-451-4359
Fax +27-41-451-1296
sales@rubiconelectrical.com

Singapore

Sentronics Automation & Marketing Pte Ltd.
Blk 3, Ang Mo Kio Industrial Park 2A
#05-06
Singapore 568050
Tel. +65-6744-8018
Fax +65-6744-1929
sentronics@pacific.net.sg

Slovakia

EUCHNER electric s.r.o.
Spielberk Office Center
Holandská
639 00 Brno
Tel. +420-533-443-150
Fax +420-533-443-153
info@euchner.cz

Slovenia

SMM d.o.o.
Jaskova 18
2000 Maribor
Tel. +386-2450-2326
Fax +386-2462-5160
franc.kit@smm.si

Spain

EUCHNER, S.L.U.
Gurutzezi 12 - Local 1
Poligono Belartza
20018 San Sebastian
Tel. +34-943-316-760
Fax +34-943-316-405
euchner@edunet.es

Sweden

Censit AB
Box 331
33123 Värnamo
Tel. +46-370-6910-10
Fax +46-370-1888-8
info@censit.se

Switzerland

EUCHNER AG
Grofstrasse 17
8887 Meis
Tel. +41-81-720-4590
Fax +41-81-720-4599
info@euchner.ch

Taiwan

Daybreak Int'l (Taiwan) Corp.
3F, No. 124, Chung-Cheng Road
Shihlin 11145, Taipei
Tel. +886-2-8866-1234
Fax +886-2-8866-1239
day111@ms23.hinet.net

Thailand

Aero Automation Co., Ltd.
600/441 Moo 14 Phaholyothin Rd.
Kukot, Lamlukka
Patumthanee 12130
Tel. +66-2-536-7660-1
Fax +66-2-536-7877
aeroautomation@yahoo.co.th

Turkey

ARI Endüstri Urunleri SAN. Ve Tic.Ltd.Sti.
Perpa Ticaret Merkezi
A Blok Kat 11 No:1406
34384 Okmeydanı/Sisli Istanbul
Tel. +90-212-3204-334
Fax +90-212-210-0201
euchner@ariendustri.com.tr

United Kingdom

EUCHNER (UK) Ltd.
Unit 2 Petre Drive,
Sheffield
South Yorkshire
S4 7PZ
Tel. +44-114-256-0123
Fax +44-114-242-5333
info@euchner.co.uk

USA

EUCHNER USA Inc.
6723 Lyons Street
East Syracuse, NY 10357
Tel. +1-315-7010-315
Fax +1-315-7010-319
info@euchner-usa.com

EUCHNER USA Inc.

Detroit Office
130 Hampton Circle
Rochester Hills, MI 48307
Tel. +1-248-537-1092
Fax +1-248-537-1095
info@euchner-usa.com

EUCHNER GmbH + Co. KG

Kohlhammerstraße 16

70771 Leinfelden-Echterdingen

Germany

Tel. +49-(0)711-7597-0

Fax +49-(0)711-753316

info@euchner.de

www.euchner.com

More than safety.



EUCHNER

AUDIN - 8, avenue de la malle - 51370 Saint Brice Courcelles
Tel : 03.26.04.20.21 - Fax : 03.26.04.28.20 - Web : <http://www.audin.fr> - Email : info@audin.fr