100-POE-SPL PoE Splitter

N-Tron Networking Series



▶▶▶ PoE Splitter

The N-Tron® 100-POE-SPL is a Power over Ethernet splitter designed to accept Ethernet with PoE via Cat5 cable and output power via terminal block and Ethernet via RJ45.

This allows devices which are not PoE capable to be connected and powered by a Cat5 cable. The 100-POE-SPL also allows legacy devices which are not PoE capable to be deployed without the need to provide a dedicated power supply. The 100-POE-SPL is ideal for use with N-Tron's 105TX-POE, 105FX-POE, 100-POE4 or other PoE sourcing equipment. The 100-POE-SPL can be ordered with 12, 24, or 48 volt DC output.



APPLICATIONS

- > Factory Automation
- > Utilities
- > SCADA
- > Security Surveillance
- > Transportation
- > Alternative Energy

PRODUCT HIGHLIGHTS

- > Compact, Industrial Design
- > Up to 5 port connections
- > High Environmental Specifications
- > N-Ring Advanced Ring Technology
- > Increased Networking Performance
- > Plug-and-Play Operation

FEATURES & BENEFITS

- > Compact, Space Saving Package
- > IEEE 802.3af Compliant
- > One RJ-45 PoE Port (Data & Power In)
- > One RJ-45 Port (Data Out)
- > Unmanaged Operation
- > Extended Environmental Specifications
 - -40°C to 85°C Operating Temperature

- > Supports up to 15.4 Watts (Cable and PSE Dependent)
- > Full Wire Speed Communications
- > Built in Transient Voltage Suppression
- > Power Status LED
- > Hardened Metal DIN-Rail Enclosure













Managed Gigabit Ethernet Industrial Switch Specifications

SWITCH PROPERTIES

Compact, Space Saving Package IEEE 802.3af Compliant

One RJ-45 PoE Port (Data & Power In)

One RJ-45 Port (Data Out) Unmanaged Operation

Extended Environmental Specifications -40°C to 85°C Operating Temperature

Supports up to 15.4 Watts (Cable and PSE Dependent)

Full Wire Speed Communications
Built in Transient Voltage Suppression

Power Status LED

Hardened Metal DIN-Rail Enclosure

POWER INPUT

Input Voltage: 46-54 VDC

Steady Output Current Under Full Load: 320 mA@48VDC Steady Input Current Under No Load: 10 mA@48V

CONNECTORS

10/100BaseTX: Eight (8) RJ45 copper ports

NETWORK MEDIA

10BaseT: >Cat3 cable 100BaseTX: >Cat5 cable

RECOMMENDED WIRING CLEARANCE

Front: 2" (5.08 cm) Top: 1" (2.54 cm)

CERTIFICATION & COMPLIANCE

Product Safety: UL/cUL: Class I, Division 2, Groups A, B, C and D; T4 UL 508, ICE and ANSI/ISA-12.12.01-2007

Emissions: EN 55011, ICES-003, FCC/CE (CFR 47, Part 15,

Subpart B, Class A)

Immunity: EN 61000-6-2/4, IEC 61000-4-2/3/4/5/6 Other: ABS type approval for shipboard applications

DNV Type Approval Certification

RoHS Compliant

IEEE 1613 for Electric Utility Substations NEMA TS1/TS2 for Traffic Control

ENVIRONMENTAL

Operating Temperature: -40°C to 85°C

MECHANICAL


Case Dimensions Height: 4" (10.2 cm) Width: 1.0" (2.6 cm)


Depth: 3.7 (9.3 cm)
Depth (incl. DIN rail mount): 3.9" (9.8 cm)


Weight (max): 0.60 lbs. (0.27 kg)

Mount: DIN Rail 35mm

DIMENSIONS







All specifications are subject to change. Consult the company website for more information.

ORDERING GUIDE

PART NUMBER	DESCRIPTION
100-POE-SPL-12	Ethernet PoE splitter, 12VDC output
100-POE-SPL-24	Ethernet PoE splitter, 24VDC output
100-POE-SPL-48	Ethernet PoE splitter, 48VDC output
100-POE-SPL-XX	Ethernet PoE splitter, Custom VDC output*
*Call for pricing	



www.redlion.net

Americas

sales@redlion.net

Asia-Pacific asia@redlion.net

Europe Middle East Africa europe@redlion.net

+1 (717) 767-6511

As the global experts in communication, monitoring and control for industrial automation and networking, Red Lion has been delivering innovative solutions for over forty years. Our award-winning technology enables companies worldwide to gain real-time data visibility that drives productivity. Product brands include Red Lion, N-Tron and Sixnet. With headquarters in York, Pennsylvania, the company has offices across the Americas, Asia-Pacific and Europe. For more information, please visit www.redlion.net. Red Lion is a Spectris company.