


BIMF LED



BIMF LED

85 dB max



BIMF LED

V ACDC	12 ÷ 24 ÷ 48 ÷ 110 ÷ 240
mA	25 12 12 10 13
dB(A)1m	85



Multifunctional sounder with LED light developed with acoustic piezoelectric capsule.

Voltages
12/240V ACDC +/-10%

Mechanical features
ABS body, washer and lock ring. Screw mounting or flush mounting through the lock ring provided (Ø 12 mm). Adapter for holes Ø 16 mm - Ø 22 mm supplied with the product.

Optical features
6 red LEDs. Steady light (with continuous sound) or flashing light (slow or fast mode) with Intermittent sound (respectively slow or fast mode).

Acoustic features
Acoustic piezoelectric capsule
Continuous sound - Slow/Fast Intermittent
selectable via dip-switch.
Sound frequency: 2500+/-500Hz




Codici / Codes

BIMF LED

12/240V ACDC

38030

38032



BIMF LED



Buzzer multifonctionnel acoustique-lumineux développé avec capsule acoustique piézoélectrique.

Tension d'utilisation
12/240V ACDC +/-10%

Caractéristiques mécaniques
Corps, rondelle et bague en ABS. Fixation par vis standards ou par bague pour installation à encastrer (Ø 12 mm). Fourni adaptateur pour trou Ø 16 mm - Ø 22 mm.

Caractéristiques optiques
6 LED rouges. Lumière fixe (avec son continu) ou clignotante (lente ou rapide) avec son pulsé (respectivement lent ou rapide).

Caractéristiques acoustiques
Capsule acoustique piézo-électrique.
Son continu - Son pulsé lent ou rapide
sélectionnables par dip-switch.
Fréquence : 2500+/-500Hz